

## APC Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

Brand : APC

Product code: SRTL1000RMXLI-NC

**Product name :** Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

APC Smart-UPS On-Line, 1000VA, Lithium-ion, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1000VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14 input and 8x IEC 320 C13 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features Battery UPS topology \* Double-conversion (Online) Hot-swap battery Output power capacity \* 1 kVA Automatic battery test 1 Output power \* 900 W Cold start Waveform \* Sine Design Input operation voltage (min) \* 220 V Form factor \* Rackmount Input operation voltage (max) \* 240 V Rack capacity 30 Input frequency \* 40/70 Hz Black, Grey 220 V Product colour \* Output operation voltage (min) I CD Output operation voltage (max) 240 V Display type LED indicators Status Output frequency 50/60 Hz 340 J International Protection (IP) code IP20 Surge energy rating Certification CE, EAC, RCM, VDE Crest factor 3:1 Emergency Power Off (EPO) 1 **Operational conditions** Noise level 50 dB Operating temperature (T-T) 0 - 40 °C Surge protection -20 - 50 °C Storage temperature (T-T) Audible alarm(s) Operating relative humidity (H-H) 0 - 95% Storage relative humidity (H-H) 0 - 95% Auto-restart Operating altitude 0 - 3000 m Ports & interfaces Non-operating altitude 0 - 15000 m AC outlet types C13 coupler **Technical details** Power plug C14 coupler Sustainability certificates Green Premium 8 AC outlet(s) AC outlets quantity USB port Weight & dimensions Serial interface 1 Width 432 mm Serial interface type RJ-45 Depth 590 mm Serial ports quantity 1 Height 128 mm Ethernet LAN (RJ-45) ports 1 Weight 25.7 ka Cabling technology 10/100Base-T Package width 600 mm SmartSlot Package depth 850 mm Package height 445 mm Battery Package weight 37.4 kg Battery technology Lithium-Ion (Li-Ion) Logistics data Battery life (max) 10 year(s) Products per pallet 6 pc(s) Battery recharge time 6 h 85078000 Harmonized System (HS) code






## Other features

Output voltage

230 V







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.