



APC Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery



Brand : APC

Product code: SRTL1500RMXLI-NC

Product name : Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery



Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

[APC Smart-UPS On-Line, 1500VA, Rackmount 3U, 230V, 8x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery:](#)

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1500VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14 input and 8x IEC 320 C13 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features		Battery	
UPS topology *	Double-conversion (Online)	Hot-swap battery	✓
Output power capacity *	1.5 kVA	Automatic battery test	✓
Output power *	1350 W	Cold start	✓
Waveform *	Sine	Design	
Input operation voltage (min) *	220 V	Form factor *	Rackmount
Input operation voltage (max) *	240 V	Rack capacity	3U
Input frequency *	40/70 Hz	Product colour *	Black, Grey
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	Status
Output frequency	50/60 Hz	International Protection (IP) code	IP20
Surge energy rating	340 J	Certification	CE, EAC, RCM, VDE
Crest factor	3:1	Operational conditions	
Emergency Power Off (EPO)	✓	Operating temperature (T-T)	0 - 40 °C
Noise level	50 dB	Storage temperature (T-T)	-20 - 50 °C
Surge protection	✓	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
Auto-restart	✓	Operating altitude	0 - 3000 m
Ports & interfaces		Non-operating altitude	0 - 15000 m
AC outlet types	C13 coupler	Technical details	
Power plug	C14 coupler	Sustainability certificates	Green Premium
AC outlets quantity	8 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	432 mm
Serial interface	✓	Depth	590 mm
Serial interface type	RJ-45	Height	128 mm
Serial ports quantity	1	Weight	25.7 kg
Ethernet LAN (RJ-45) ports	1	Package width	600 mm
Cabling technology	10/100Base-T	Package depth	850 mm
SmartSlot	✓	Package height	445 mm
Battery		Package weight	37.4 kg
Battery technology	Lithium-Ion (Li-Ion)	Logistics data	
Battery life (max)	10 year(s)	Products per pallet	6 pc(s)
Battery recharge time	6 h	Harmonized System (HS) code	85078000

Other features

Output voltage 230 V



0731304346418



731304346418



8592978108717

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.