



## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 10 kVA 10000 W 10 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SRT10KXLI

**Tuotteen nimi :** Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 10 kVA, Lähtöteho: 10000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Pääte, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 1805 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,8 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, International Protection (IP)-koodi: IP20. Tuotteen leveys: 263 mm, Tuotteen syvyys: 715 mm, Tuotteen korkeus: 432 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	10 kVA	<b>Design</b>	
Output power *	10000 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	100 V	LED indicators	✓
Input operation voltage (max) *	476 V	International Protection (IP) code	IP20
Input frequency *	40/70 Hz	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE, REACH
Output operation voltage (min)	220 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	480 J	Operating relative humidity (H-H)	0 - 95%
Number of output phases	1	Storage relative humidity (H-H)	0 - 95%
Efficiency	94.6%	Operating altitude	0 - 3000 m
Crest factor	3:1	Non-operating altitude	0 - 15000 m
Emergency Power Off (EPO)	✓	<b>Technical details</b>	
Noise level	55 dB	Sustainability certificates	ENERGY STAR
Audible alarm(s)	✓	Compliance certificates	RoHS
Auto-restart	✓	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	263 mm
AC outlet types	C13 coupler, C19 coupler	Depth	715 mm
Power plug	Terminal	Height	432 mm
AC outlets quantity	10 AC outlet(s)	Weight	111.8 kg
Number of output IEC jumpers	3	Package width	600 mm
USB port	✓	Package depth	1000 mm
Serial interface	✓	Package height	461 mm
Serial interface type	RJ-45		
SmartSlot	✓		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	126.8 kg
Battery capacity	1805 VAh	<b>Packaging data</b>	
Typical backup time at full load	3.8 min	Cables included	USB cable
Typical backup time at half load	11.5 min	Temperature sensor	✓
Battery life (max)	5 year(s)	Quick installation guide	✓
Battery recharge time	1.5 h	Warranty card	✓
Hot-swap battery	✓	Software CD	✓
Automatic battery test	✓	<b>Logistics data</b>	
		Harmonized System (HS) code	85078000
		<b>Other features</b>	
		Interface	RJ-45 10/100 Base-T
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Packaging content	Web/SNMP Management Card



0731304304272



731304304272

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.