



## APC SRT3000XLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2700 W 10 AC-pistorasia(a)

Tuotemerkki : APC


Tuotekoodi: SRT3000XLI

Tuotteen nimi : SRT3000XLI

APC SRT3000XLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 505 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Tower, Tuotteen väri: musta, Johdon pituus: 2,44 m. Tuotteen leveys: 85 mm, Tuotteen syvyys: 635 mm, Tuotteen korkeus: 432 mm



Runtime Graph




Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	3 kVA	Cold start	✓
Output power *	2700 W	<b>Design</b>	
Waveform *	Sine	Form factor *	Tower
Input operation voltage (min) *	100 V	Cable length	2.44 m
Input operation voltage (max) *	275 V	Product colour *	Black
Input frequency *	40/70 Hz	Display type	LCD
Output operation voltage (min)	220 V	LED indicators	✓
Output operation voltage (max)	240 V	International Protection (IP) code	IP20
Output frequency	50/60 Hz	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Output frequency regulation	50/60 Hz	<b>Operational conditions</b>	
Surge energy rating	340 J	Operating temperature (T-T)	0 - 40 °C
Efficiency	93.5%	Storage temperature (T-T)	-15 - 45 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
Noise level	55 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	<b>Technical details</b>	
Web-based management	✓	Sustainability certificates	ENERGY STAR, Green Premium
Auto-restart	✓	Compliance certificates	RoHS
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
AC outlet types	C13 coupler, C19 coupler	Width	85 mm
Power plug	C20 coupler	Depth	635 mm
AC outlets quantity	10 AC outlet(s)	Height	432 mm
Number of output IEC jumpers	2	Weight	31.3 kg
USB port	✓	Package width	599 mm
Serial interface	✓	Package depth	871 mm
Serial interface type	RJ-45		
SmartSlot	✓		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery capacity	505 VAh	Package weight	36.7 kg
Number of batteries supported	1	<b>Packaging data</b>	
Typical backup time at full load	4 min	Rack mount kit	✓
Typical backup time at half load	11.8 min	Bracket	✓
Battery life (max)	5 year(s)	Cables included	USB cable
Battery recharge time	3 h	Quick installation guide	✓
Hot-swap battery	✓	Warranty card	✓
		Software CD	✓
		<b>Logistics data</b>	
		Harmonized System (HS) code	85078000
		<b>Other features</b>	
		Output voltage	230 V
		Packaging content	Country-specific detachable power cord Removable support feet



0731304317678



731304317678

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.