

APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 5 kVA 4500 W 10 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SRT5KRMXLI

Tuotteen nimi: Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 5 kVA, Lähtöteho: 4500 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 845 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 3U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE






Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	5 kVA	Replacement battery cartridge	APCRBC140
Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency *	yeform * It operation voltage (min) * It operation voltage (max) * It frequency regulation It frequency regulation It frequency regulation It frequency * It frequency	Design	
		Form factor * Rack capacity Product colour * Display type	Rackmount 3U Black LCD
Output operation voltage (max)		Operational conditions	
Output frequency regulation Surge energy rating Efficiency Crest factor Emergency Power Off (EPO) Output voltage Total Harmonic		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Distortion (THD)		Certificates	
Noise level	55 dB	Compliance certificates	RoHS
Surge protection Audible alarm(s) Auto-restart	V V V	Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Ports & interfaces		Packaging content	
AC outlet types	C13 coupler, C19 coupler	Rack mount kit	✓
Power plug	Hardwire	Quick installation guide	✓
AC outlets quantity	10 AC outlet(s)	Sustainability	
Number of output IEC jumpers	2	Sustainability certificates	ENERGY STAR
USB port	✓	·	ENERGI STAR
Serial interface	✓	Weight & dimensions	
Serial interface type	RJ-45	Width	432 mm
SmartSlot	✓	Depth	719 mm
Battery		Height Weight	130 mm 54.4 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	34.4 Kg
Battery capacity	845 VAh		
Typical backup time at full load	4 min	Temperature sensor	✓
Typical backup time at half load	11.8 min	Warranty card	√
Battery life (max)	5 year(s)	Package width	610 mm
Battery recharge time	1.5 h	Package depth	960 mm
Hot-swap battery	V	Package height Package weight	330 mm 66.9 kg
Automatic battery test	✓	i dekage weight	56.5 kg

Logistics data

Products per pallet 6 pc(s)
Harmonized System (HS) code 85078000
Total carbon footprint (kg of CO2e) 8408.59

Other features

Packaging content Web/SNMP Management Card





731304301196

0731304301196

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.