



APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 5 kVA 4500 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRT5KRMXLI

Tuotteen nimi : Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 5 kVA, Lähtöteho: 4500 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 845 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 3U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE



Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	5 kVA	Replacement battery cartridge	APCRBC140
Output power *	4500 W	Design	
Waveform *	Sine	Form factor *	Rackmount
Input operation voltage (min) *	100 V	Rack capacity	3U
Input operation voltage (max) *	275 V	Product colour *	Black
Input frequency *	40 - 70 Hz	Display type	LCD
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	480 J	Operating relative humidity (H-H)	0 - 95%
Efficiency	94.1%	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Output voltage Total Harmonic Distortion (THD)	3%	Certificates	
Noise level	55 dB	Compliance certificates	RoHS
Surge protection	✓	Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Audible alarm(s)	✓	Packaging content	
Auto-restart	✓	Rack mount kit	✓
Ports & interfaces		Quick installation guide	✓
AC outlet types	C13 coupler, C19 coupler	Sustainability	
Power plug	Hardwire	Sustainability certificates	ENERGY STAR
AC outlets quantity	10 AC outlet(s)	Weight & dimensions	
Number of output IEC jumpers	2	Width	432 mm
USB port	✓	Depth	719 mm
Serial interface	✓	Height	130 mm
Serial interface type	RJ-45	Weight	54.4 kg
SmartSlot	✓	Packaging data	
Battery		Temperature sensor	✓
Battery technology	Sealed Lead Acid (VRLA)	Warranty card	✓
Battery capacity	845 VAh	Package width	610 mm
Typical backup time at full load	4 min	Package depth	960 mm
Typical backup time at half load	11.8 min	Package height	330 mm
Battery life (max)	5 year(s)	Package weight	66.9 kg
Battery recharge time	1.5 h		
Hot-swap battery	✓		
Automatic battery test	✓		

Logistics data

Products per pallet	6 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	8408.59

Other features

Packaging content	Web/SNMP Management Card
-------------------	--------------------------



0731304301196



731304301196

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.