



APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 8 kVA 8000 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRT8KRMXLI

Tuotteen nimi : Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 8 kVA, Lähtöteho: 8000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Pääte, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 1728 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 5,2 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 6U. Tuotteen leveys: 715 mm, Tuotteen syvyys: 432 mm, Tuotteen korkeus: 263 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Hot-swap battery	✓
Output power capacity *	8 kVA	Automatic battery test	✓
Output power *	8000 W	Cold start	✓
Waveform *	Sine		
Input operation voltage (min) *	100 V		
Input operation voltage (max) *	476 V		
Input frequency *	40 - 70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency regulation	50/60 Hz		
Surge energy rating	480 J		
Number of output phases	1		
Efficiency	94.8%		
Crest factor	3:1		
Emergency Power Off (EPO)	✓		
Output voltage Total Harmonic Distortion (THD)	3%		
Noise level	55 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler	Form factor *	Rackmount/Tower
Power plug	Terminal	Rack capacity	6U
AC outlets quantity	10 AC outlet(s)	Product colour *	Black
Number of output IEC jumpers	3	Display type	LCD
USB port	✓	LED indicators	Status
Serial interface	✓		
		Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	715 mm
		Depth	432 mm
		Height	263 mm
		Weight	111.8 kg
		Package width	600 mm

Ports & interfaces		Weight & dimensions	
Serial interface type	RJ-45	Package depth	1000 mm
SmartSlot	✓	Package height	461 mm
Battery		Package weight	130 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Battery capacity	1728 VAh	Rack mount kit	✓
Typical backup time at full load	5.2 min	Bracket	✓
Typical backup time at half load	14.5 min	Cables included	USB cable
Battery life (max)	5 year(s)	Temperature sensor	✓
Battery recharge time	1.5 h	Quick installation guide	✓
		Warranty card	✓
		Software CD	✓
		Logistics data	
		Products per pallet	1 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Packaging content	Web/SNMP Management Card



0731304304296



731304304296

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.