




APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 10 kVA 10000 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRT10KRMXLI

Tuotteen nimi : Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 10 kVA, Lähtöteho: 10000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Pääte, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 1805 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,8 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 6U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 715 mm, Tuotteen korkeus: 263 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	10 kVA	Design	
Output power *	10000 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Rack capacity	6U
Input operation voltage (min) *	100 V	Product colour *	Black
Input operation voltage (max) *	476 V	Display type	LCD
Input frequency *	40 - 70 Hz	LED indicators	✓
Output operation voltage (min)	220 V	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE, REACH
Output operation voltage (max)	240 V	Operational conditions	
Output frequency regulation	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	480 J	Storage temperature (T-T)	-15 - 45 °C
Number of output phases	1	Operating relative humidity (H-H)	0 - 95%
Efficiency	94.6%	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Output voltage Total Harmonic Distortion (THD)	3%	Technical details	
Noise level	55 dB	Sustainability certificates	ENERGY STAR
Surge protection	✓	Compliance certificates	RoHS
Audible alarm(s)	✓	Weight & dimensions	
Auto-restart	✓	Width	432 mm
Ports & interfaces		Depth	715 mm
AC outlet types	C13 coupler, C19 coupler	Height	263 mm
Power plug	Terminal	Weight	111.8 kg
AC outlets quantity	10 AC outlet(s)	Package width	600 mm
Number of output IEC jumpers	3	Package depth	1000 mm
USB port	✓		
Serial interface	✓		

Ports & interfaces		Weight & dimensions	
Serial interface type	RJ-45	Package height	461 mm
SmartSlot	✓	Package weight	130 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit	✓
Battery capacity	1805 VAh	Bracket	✓
Typical backup time at full load	3.8 min	Cables included	USB cable
Typical backup time at half load	11.5 min	Temperature sensor	✓
Battery life (max)	5 year(s)	Quick installation guide	✓
Battery recharge time	3 h	Warranty card	✓
Hot-swap battery	✓	Software CD	✓
Automatic battery test	✓		
Logistics data			
Harmonized System (HS) code		85078000	
Other features			
Interface		RJ-45 10/100 Base-T	
Nominal output voltage		230 V	
Nominal input voltage		230 V	
Packaging content		Web/SNMP Management Card	



0731304304265



731304304265

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.