



## APC Smart-UPS UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 2,2 kVA 1980 W 10 AC-pistorasia(a)



**Tuotemerkki :** APC

**Tuotekoodi:** SRT2200RMXLI

**Tuotteen nimi :** Smart-UPS

APC Smart-UPS. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1980 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 367 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 3,9 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 584 mm, Tuotteen korkeus: 85 mm


Features		Battery	
UPS topology *	Double-conversion (Online)	Cold start	✓
Output power capacity *	2.2 kVA	<b>Design</b>	
Output power *	1980 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Rack capacity	2U
Input operation voltage (min) *	100 V	Cable length	2.44 m
Input operation voltage (max) *	275 V	Product colour *	Black
Input frequency *	40/70 Hz	Display type	LCD
Output operation voltage (min)	220 V	LED indicators	✓
Output operation voltage (max)	240 V	International Protection (IP) code	IP20
Output frequency regulation	50/60 Hz	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Surge energy rating	340 J	<b>Operational conditions</b>	
Efficiency	92.2%	Operating temperature (T-T)	0 - 40 °C
Crest factor	3:1	Storage temperature (T-T)	-20 - 50 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Noise level	55 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Web-based management	✓	<b>Technical details</b>	
Auto-restart	✓	Sustainability certificates	ENERGY STAR, Green Premium
<b>Ports &amp; interfaces</b>		Compliance certificates	RoHS
AC outlet types	C13 coupler, C19 coupler	<b>Weight &amp; dimensions</b>	
Power plug	C20 coupler	Width	432 mm
AC outlets quantity	10 AC outlet(s)	Depth	584 mm
Number of output IEC jumpers	2	Height	85 mm
USB port	✓	Weight	25 kg
Serial interface	✓	Package width	599 mm
Serial interface type	RJ-45	Package depth	810 mm
SmartSlot	✓	Package height	246 mm
<b>Battery</b>		Package weight	34 kg
Battery technology	Sealed Lead Acid (VRLA)	<b>Packaging data</b>	
Battery capacity	367 VAh	Rack mount kit	✓
Number of batteries supported	1	Bracket	✓
Typical backup time at full load	3.9 min	Cables included	USB cable
Typical backup time at half load	11.6 min	Quick installation guide	✓
Battery life (max)	5 year(s)	Software CD	✓
Battery recharge time	3 h	<b>Logistics data</b>	
Hot-swap battery	✓	Products per pallet	12 pc(s)
Automatic battery test	✓	Harmonized System (HS) code	85078000

**Other features**

Nominal output voltage	230 V
Nominal input voltage	230 V



0731304317623



731304317623

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.