



APC Smart-UPS On-Line SRT UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 3 kVA 2700 W



Tuotemerkki : APC

Tuotekoodi: SRT3000RMXLI-NC

Tuotteen nimi : Smart-UPS On-Line SRT

APC Smart-UPS On-Line SRT. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Sarjaliitännän tyyppi: RJ-45. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 505 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 4 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 635 mm, Tuotteen korkeus: 85 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Battery recharge time	3 h
Output power capacity *	3 kVA	Hot-swap battery	✓
Output power *	2700 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	100 V	Design	
Input operation voltage (max) *	275 V	Form factor *	Rackmount
Input frequency *	40 - 70 Hz	Rack capacity	2U
Output operation voltage (min)	220 V	Cable length	2.44 m
Output operation voltage (max)	240 V	Product colour *	Black
Output frequency	50/60 Hz	Display type	LCD
Automatic Voltage Regulation (AVR)	✓	LED indicators	Battery replacement
Surge energy rating	340 J	International Protection (IP) code	IP20
Efficiency	92%	Certification	CE, VDE, RCM, EAC, IEC/EN 62040-1, IEC/EN 62040-2, UL-1778, FCC 15 A, CSA
Crest factor	3:1	Operational conditions	
Emergency Power Off (EPO)	✓	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	2%	Storage temperature (T-T)	-15 - 45 °C
Noise level	55 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Power protection features	Overload	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Audible alarm modes	Battery replacement	Technical details	
Auto-restart	✓	Sustainability certificates	Green Premium
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	C13 coupler, C19 coupler	Weight & dimensions	
Power plug	C20 coupler	Width	432 mm
USB port	✓	Depth	635 mm
Serial interface	✓	Height	85 mm
Serial interface type	RJ-45	Weight	31.3 kg
SmartSlot	✓	Package width	599 mm
Battery		Package depth	871 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	246 mm
Battery capacity	505 VAh	Package weight	39.3 kg
Typical backup time at full load	4 min	Packaging data	
Typical backup time at half load	11.8 min	Quick installation guide	✓
Battery life (max)	5 year(s)	Logistics data	
		Products per pallet	6 pc(s)

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Other features

Output voltage	230 V
----------------	-------



0731304327592



731304327592

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.