

ZYXEL

## Zyxel WAC500H 1200 Mbit/s Valkoinen Power over Ethernet -tuki

**Tuotemerkki :** Zyxel

**Tuotekoodi:** WAC500H-EU0101F

**Tuotteen nimi :** WAC500H

Zyxel WAC500H. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1200 Mbit/s. Tietoturva-algoritmit: EAP, SNMP, WEP, WPA, WPA2-Enterprise, WPA2-PSK, WPA3. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Power	
2.4 GHz *	✓	Output voltage	12 V
5 GHz *	✓	Output current	1 A
Maximum data transfer rate *	1200 Mbit/s	<b>Design</b>	
Maximum data transfer rate (2.4 GHz)	300 Mbit/s	Placement *	Wall
Maximum data transfer rate (5 GHz)	866 Mbit/s	Product colour *	White
Ethernet LAN data rates	10,100,1000 Mbit/s	<b>Antenna</b>	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at	Antenna type *	Internal
		Antenna gain level (max)	4 dBi
	<b>Certificates</b>		
			FCC 15C, FCC 15E; ETSI EN 300 328, EN 301 893; LP0002, EN 60601-1-2 FCC 15B, EN 301 489-1; EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, BSMI CNS13438 EN 60950-1, IEC 60950-1; BSMI CNS14336-1
Channel bandwidth	80 MHz	<b>Weight &amp; dimensions</b>	
MIMO	✓	Width	173 mm
MIMO type	Multi User MIMO	Depth	97 mm
Wi-Fi Multimedia (WMM)/(WME)	✓	Height	29 mm
Fast roaming	✓	Weight	223 g
VLAN support	✓	<b>Packaging data</b>	
Wireless isolation	✓	Package width	195 mm
Band steering	✓	Package depth	120 mm
Transmitting power	26 dBmW	Package height	53 mm
Receiver sensitivity	-99 dBm	Package weight	444 g
<b>Security</b>		<b>Packaging content</b>	
Security algorithms *	EAP, SNMP, WEP, WPA, WPA2-Enterprise, WPA2-PSK, WPA3	Quantity per pack	1 pc(s)
MAC address filtering	✓		
Auto Wireless Distribution System (WDS)	✓		

<b>Management features</b>		<b>Packaging content</b>	
Web-based management	✓	Mounting kit	✓
Command-line interface (CLI)	✓	<b>Operational conditions</b>	
<b>Ports &amp; interfaces</b>		Operating relative humidity (H-H)	10 - 90%
Ethernet LAN (RJ-45) ports *	3	Operating temperature (T-T)	0 - 50 °C
DC-in jack	✓	Storage temperature (T-T)	-30 - 70 °C
<b>Power</b>		Storage relative humidity (H-H)	10 - 90%
Power over Ethernet (PoE) *	✓	<b>Logistics data</b>	
AC input voltage	100 - 240 V	Harmonized System (HS) code	85176990
AC input frequency	50 - 60 Hz		
Input current	0.3 A		



4718937615209



4172937615209

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.