

Delock Adapter USB Type-C™ Stecker > VGA / HDMI / DVI Buchse schwarz

Description

This adapter by Delock is suitable for the connection of a VGA, HDMI or DVI monitor to a computer with USB-C™ interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface. Only one monitor can be used on the adapter.



Specification

- Connectors:
 - 1 x USB Type-C™ male >
 - 1 x VGA 15 pin female
 - 1 x HDMI-A 19 pin female
 - 1 x DVI 24+1 female with nuts
- Chipset: VL100, IT6562FN, PS8222B
- High Speed HDMI specification
- DVI-D (Single Link), VGA not wired
- Only 1 monitor usable with the adapter
- Resolution:
 - HDMI up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
 - DVI and VGA up to 1920 x 1080 @ 60 Hz (depending on the system and the connected hardware)
- Power consumption: max. 1.35 W
- Cable length without connectors: ca. 13 cm
- Colour: black

System requirements

- Linux Kernel 4.6 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- Adapter USB-C™ to VGA / HDMI / DVI

Item no. 63925

EAN: 4043619639250

Country of origin: China

Package: Retail Box



Images



General

Supported operating system:	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Mac OS 10.13.3 or above
Linux Kernel 4.6 or above	

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x HDMI-A 19 pin female
connector 3:	1 x DVI 24+1 female with nuts
connector 4:	1 x VGA 15 pin female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 30 Hz
	1920 x 1080 @ 60 Hz
Maximum power consumption:	1.35 W

Physical characteristics

Ferrite core:	1 x
Colour:	black