

## BenQ SL6502K 165,1 cm (65") LED 500 cd/m<sup>2</sup> 4K Ultra HD musta Sisäänrakennettu prosessori Android

Tuotemerkki : BenQ

Tuotekoodi: 9H.F68PK.NA2

Tuotteen nimi : SL6502K

BenQ SL6502K. Näytön halkaisija: 165,1 cm (65"), Näytön teknologia: LED, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 500 cd/m<sup>2</sup>, HD-tyyppi: 4K Ultra HD. Käyttöjärjestelmä asennettu: Android. Tuotteen väri: musta





Display		Design	
LED backlighting type Display diagonal * Display technology * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio Contrast ratio (typical) Viewing angle, horizontal Viewing angle, vertical Active display area (W x H) Panel life	Direct-LED 165.1 cm (65") LED 3840 x 2160 pixels 500 cd/m <sup>2</sup> 4K Ultra HD × 16:9 1200:1 178° 178° 178° 1428.5 x 803.5 mm 50000 h	Orientation Product colour * VESA mounting * Panel mounting interface Performance On Screen Display (OSD) Number of OSD languages On Screen Display (OSD) languages	Horizontal/Vertical Black 400 x 400 mm 26 Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Persian, Polish,
Ports & interfaces	50000 11		Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese
HDMI ports quantity *	2	Power	
DVI port * VGA (D-Sub) input ports DisplayPorts quantity * USB port *	× 1 1	Power consumption (typical) * Power consumption (standby) * AC input voltage AC input frequency	225 W 0.5 W 100 - 240 V 50 - 60 Hz
USB ports quantity	4	Computer system	
Ethernet LAN * Ethernet LAN (RJ-45) ports Wi-Fi * RS-232 interface	✓ 1 ×	Computer system * Built-in processor * Internal memory Internal storage capacity	× ✓ 4 GB 32 GB
Audio		Operating system installed	Android
Built-in speaker(s) * Number of built-in speakers	✓ 2	Weight & dimensions Width	1454.6 mm

Audio		Weight & dimensions	
RMS rated power	20 W	Depth Height Weight	72 mm 829.6 mm 35.5 kg
		Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -10 - 60 °C





4718755081057

4544438080518

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.