

## be quiet! Straight Power 11 virtalähdeyksikkö 750 W 20+4 pin ATX ATX musta

**Tuotemerkki** : be quiet!

**Tuotekoodi**: BN283

**Tuotteen nimi** : Straight Power 11

be quiet! Straight Power 11. Kokonaisteho: 750 W, AC-syöttöjännite: 100 - 240 V, Huipputeho: 820 W. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 60 cm, SATA-virtakaapelin pituus: 550 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Tuulettimen halkaisija: 13,5 cm, Tuulettimien määrä: 1 tuuletin(ta). Tuotteen leveys: 150 mm, Tuotteen syvyys: 170 mm, Tuotteen korkeus: 86 mm



Power		Performance	
Total power *	750 W	80 PLUS certification *	80 PLUS Gold
Peak power	820 W	Purpose *	PC
AC input voltage *	100 - 240 V	Power supply unit (PSU) form factor *	ATX
AC input frequency	50 - 60 Hz	ATX version	2.4
Input current	10 A	EPS version	2.92
Power factor	0.99	Silent mode	✓
Power Factor Correction (PFC) type	Active	Bearing technology	FDB
Combined power (+3.3V)	150 W	Certification	CE, FCC, TÜV, cTUVus, RCM, BSMI, CU
Combined power (+12V)	750 W	Design	
Combined power (+5V)	150 W	Product colour	Black
Combined power (-12V)	6 W	Fan diameter	13.5 cm
Combined power (+5Vsb)	15 W	Number of fans	1 fan(s)
Max output current (+3.3V)	25 A	Illumination	✗
Max output current (+12V1)	20 A	On/off switch	✓
Max output current (+12V2)	20 A	Weight & dimensions	
Max output current (+12V3)	24 A	Width	150 mm
Max output current (+12V4)	24 A	Depth	170 mm
Max output current (+5V)	25 A	Height	86 mm
Max output current (-12V)	0.5 A	Weight	1.78 kg
Max output current (+5Vsb)	3 A	Packaging data	
Hold time	19.6 ms	Manual	✓
Efficiency	93%	Package width	248 mm
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Package depth	328 mm
Ports & interfaces		Package height	102 mm
Motherboard power connector *	20+4 pin ATX	Package weight	3.34 kg
Motherboard power cable length	60 cm		
Number of SATA power connectors	11		
Number of PATA power connectors	4		

Ports & interfaces		Technical details	
SATA power cable length	550 mm	Sustainability certificates	ENERGY STAR
PCI Express power connectors (6+2 pin)	4	Compliance certificates	RoHS
PCI Express power cable length	60 cm	<b>Logistics data</b>	
CPU power connector (4+4 pin)	✓	Harmonized System (HS) code	84733020
CPU power cable length	70 cm	<b>Other features</b>	
Floppy disk drive connector	✓	Screws included	✓
Cabling type	Fully-Modular	Cable ties included	✓
		Noise level (silent mode, <30%)	8.4 dB
		Noise level (quiet mode, 50%)	9.01 dB
		Noise level (full-load mode, 100%)	21.23 dB
		Cable management	✓



4260052185780

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-DEC-2024. Prints or copies of Information are only valid on the printed Publication date