

Lenovo

Lenovo 40A90090EU kannettavien tietokoneiden telakka ja porttitoistin Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-C musta

Tuotemerkki : Lenovo

Tuotekoodi: 40A90090EU

Tuotteen nimi : 40A90090EU

Lenovo 40A90090EU. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB-liitin: USB A-tyyppi, USB Type-C. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Tuotteen väri: musta, Kaapelilukon aukkotyyppi: Kensington, Tuotemerkin yhteensopivuus: Lenovo. Virtalähteen malli: AC, Virtalähde: 90 W, Virtalähteen tyyppi: Ulkoinen. Tuotteen leveys: 171 mm, Tuotteen syvyys: 80 mm, Tuotteen korkeus: 32,5 mm



Ports & interfaces		Performance		
Connectivity technology *	Wired	Compatibility	A475, A275, E585, E485, E580, E480, E570,L380 Yoga, L380, L580, L480, Lenovo tablet 10, Miix 720, Miix 520, Miix 510, Miix 510, T580, T570, T480, T480s, T470, T470s, X1 Tablet Gen 3,X1 Tablet Gen 2, X1 Tablet Gen 1, X1 Carbon Gen 6, X1 Carbon Gen 5, X1 Yoga Gen 3, X1 Yoga Gen 2, X380 Yoga, X280, X270,Yoga 370, 13 Gen 2 Windows, 13 Gen 1 Windows, 11e Gen 5, Yoga 11e Gen 5,	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C			
USB 2.0 ports quantity *	2			
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3			
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1			
VGA (D-Sub) ports quantity	1			
DisplayPorts quantity	2			
Combo headphone/mic port	✓			
USB connector type	USB Type-A, USB Type-C			
DC-in jack	✓			
Network		Certification	CB,CULUS,EAC,TUV Mark,FCC,ICES, DOC, NOM,KCC, RCM, BSMI, VCCI, CE, LoA	
Ethernet LAN *	✓			
Ethernet LAN (RJ-45) ports	1			
Ethernet LAN data rates	10,100,1000 Mbit/s			
Wake-on-LAN ready	✓			
10G support	✗			
Performance		Power	Power source type	AC
Card reader integrated *	✗			
Number of displays supported	2			
Cable lock slot	✓			
Cable lock slot type	Kensington			
Product colour *	Black			
Brand compatibility	Lenovo			
		Operational conditions	Power supply	90 W
			Power supply type	External
			Power plug type	Type C
		Weight & dimensions	Compatible power plug types	EU
			Operating temperature (T-T)	-5 - 40 °C
			Operating relative humidity (H-H)	20 - 95%
		Packaging content	Width	171 mm
			Depth	80 mm
			Height	32.5 mm
		Logistics data	Cables included	AC, USB Type-C
			AC adapter included	✓
		Harmonized System (HS) code	84733020	



0190725798969



190725798969

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.