

ZYXEL

Zyxel GS1900-48HPv2 Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta




Tuotemerkki : Zyxel

Tuotekoodi: GS190048HPV2-EU0101F

Tuotteen nimi : GS1900-48HPv2

Zyxel GS1900-48HPv2. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 100 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE.... Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki. Telineasennus

Management features		Design	
Switch type *	Managed	LED indicators	✓
Switch layer	L2	Performance	
Quality of Service (QoS) support	✓	Noise level	36.9 dB
MIB support	RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215, RFC 1493	Power	
Ports & interfaces		AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports quantity *	48	AC input frequency	50 - 60 Hz
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power consumption (max)	220.5 W
SFP module slots quantity	2	Power over Ethernet (PoE)	
Power connector	DC-in jack	Power over Ethernet (PoE) *	✓
Network		Power over Ethernet (PoE) ports quantity	24
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Total Power over Ethernet (PoE) budget	170 W
Copper ethernet cabling technology	1000BASE-T	Operational conditions	
Full duplex	✓	Operating temperature (T-T)	0 - 50 °C
VLAN support	✓	Storage temperature (T-T)	-40 - 70 °C
Data transmission		Operating relative humidity (H-H)	10 - 95%
Switching capacity *	100 Gbit/s	Weight & dimensions	
MAC address table *	8000 entries	Width	441 mm
Store-and-forward	✓	Depth	270 mm
Jumbo frames support	✓	Height	44 mm
Design		Weight	3.55 kg
Rack mounting *	✓	Certificates	
Product colour	Black	Certification	RoHS, CE
		Logistics data	
		Harmonized System (HS) code	85176990



4718937609543



5054444595955

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.