Chieftec Smart 300W virtalähdeyksikkö 20+4 pin ATX TFX Harmaa

Tuotemerkki : Chieftec Tuotekoodi: GPF-300P

Tuotteen nimi: Smart 300W


Chieftec Smart 300W. Kokonaisteho: 300 W, AC-syöttöjännite: 115 - 230 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 30 cm, SATA-virtakaapelin pituus: 150,350 mm. Tarkoitus: PC/palvelin, Virransyöttöyksikön mitat: TFX, 80 PLUS certification: 80 PLUS Bronze. Tuotteen väri: Harmaa, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 8 cm. Tuotteen leveys: 85 mm, Tuotteen syvyys: 175 mm, Tuotteen korkeus: 65 mm





Power		Ports & interfaces	
Total power * 300 W AC input voltage * 115 - 230 V AC input frequency 47 - 63 Hz Input current 6.3 A Power factor 0.9 Power Factor Correction (PFC) type Active Combined power (+3.3V) 95 W Combined power (+5V) 95 W Combined power (-12V) 3.6 W Combined power (+5Vsb) 10 W Max output current (+3.3V) 16 A Max output current (+12V1) 14 A Max output current (+12V2) 15 A Max output current (+5V) 15 A Max output current (-12V) 0.3 A Max output current (+5Vsb) 2 A Over voltage, Overheating, Overload, Short circuit, Under	115 - 230 V 47 - 63 Hz 6.3 A 0.9	EPS power connector (4+4 pin) CPU power cable length Floppy drive power connector Floppy disk drive cable length Cabling type	35 cm 1 15 cm Non-Modular
	95 W 95 W 3.6 W 10 W	Performance 80 PLUS certification * Purpose * Power supply unit (PSU) form factor * ATX version	80 PLUS Bronze PC/Server TFX 2.3
	Product colour Cooling type Fan diameter Number of fans Weight & dimensions	Grey Active 8 cm 1 fan(s)	
Ports & interfaces Motherboard power connector * 20+4 pin ATX Motherboard power cable length 30 cm Number of SATA power connectors 4 SATA power cable length 150,350 mm Peripheral (Molex) power connectors (4-pin) * 2 Peripheral (Molex) power cable length 150,350 mm	20+4 pin ATX 30 cm	Width 85 mm Depth 175 mm Height 65 mm	85 mm 175 mm 65 mm 1.07 kg
	150,350 mm 2	Packaging data Package weight Technical details Compliance certificates Logistics data	1.13 kg RoHS
		Harmonized System (HS) code	84733020





4710713234666

5715063383896

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.