## Chieftec PowerUp Chieftronic virtalähdeyksikkö 650 W 20+4 pin ATX ATX musta

Tuoteperhe: PowerUp

Tuotemerkki : Chieftec

Tuoteko

Tuotekoodi: GPX-650FC

Tuotteen nimi : Chieftronic PowerUp

Chieftec PowerUp Chieftronic. Kokonaisteho: 650 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 500,650,800 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 86 mm






|                                |   | Ports & interfaces                     |                            |
|--------------------------------|---|--|----------------------------|
|                                | 50 W<br>00 - 240 V  | PCI Express power connectors (6+2 pin) | 2                          |
| - 5 -                          | 7 - 63 Hz   | PCI Express power cable length         | 50 cm                      |
| t 10 /                         |   | CPU power connector (4+4 pin)          | 1                          |
|                                | ctive   | CPU power cable length                 | 80 cm                      |
| ( ))                           | 00 W  | Floppy drive power connector           | 1                          |
|                                | 48 W  | PCI Express connector                  | 1                          |
| ( )                            | 00 W  | Cabling type                           | Fully-Modular              |
|                                | 6 W   | 0.71                                   |                            |
|                                | 2.5 W   | Performance                            |                            |
| current (+3.3V) 20 A           | Α   | 80 PLUS certification *                | 80 PLUS Gold               |
| current (+12V) 54 A            | 4 A   | Purpose *                              | PC                         |
| current (+5V) 20 A             | A   | Power supply unit (PSU) form factor    | ATX                        |
| current (-12V) 0.3             | 3 A   | ATX version                            | 2.53                       |
| current (+5Vsb) 2.5            | 5 A   | Certification                          | 80PLUS Gold                |
|                                | Over current, Over power, Over<br>voltage, Overheating, Short circuit,<br>Under voltage |  |                            |
|                                |   | Design                                 |                            |
|                                |   | Product colour                         | Black                      |
| erfaces                        |   | Cooling type                           | Active                     |
| power connector * 20+          | 0+4 pin ATX   | Fan diameter                           | 12 cm                      |
| l power cable length 65 d      | 5 cm  | Number of fans                         | 1 fan(s)                   |
| ATA power connectors 9         |   | Weight & dimensions                    |                            |
| cable length 500               | 00,650,800 mm   | Width                                  | 150 mm                     |
| ٥lex) power 3<br>4-pin) *      |   | Depth                                  | 140 mm                     |
| Iolex) power cable             | 00 650 800 050 mm   |  |                            |
| 500                            | 0,000,800,900 11111   | Weight                                 | 2.2 kg                     |
|                                |   | Packaging data                         |                            |
|                                |   | Package weight                         | 2.75 kg                    |
| 4-pin) *<br>Aolex) nower cable | 00,650,800,950 mm   | Height<br>Weight<br>Packaging data     | 86 mm<br>2.2 kg<br>2.75 kg |

## Logistics data

Harmonized System (HS) code

84733020





753263077189

0753263077189

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.