



## BenQ SL7502K 190.5 cm (75") LED 500 cd/m<sup>2</sup> 4K Ultra HD Black Android 8.0

**Brand :** BenQ

**Product code:** 9H.F69PK.NA2

**Product name :** SL7502K




75" DLED, 3840x2160px, 500 cd/m<sup>2</sup>, 1200:1, 2x 16W, 3x HDMI 2.0, VGA, DisplayPort 1.1/1.2, 2x USB 2.0, 2x USB 3.0, RJ-45, Android 8.0

BenQ SL7502K. Display diagonal: 190.5 cm (75"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m<sup>2</sup>, HD type: 4K Ultra HD. Operating system installed: Android 8.0. Product colour: Black



Display		Audio	
Panel type	IPS	Number of built-in speakers	2
LED backlighting type	Direct-LED	RMS rated power	32 W
Display diagonal *	190.5 cm (75")	<b>Design</b>	
Display technology *	LED	Orientation	Horizontal/Vertical
Display resolution *	3840 x 2160 pixels	Product colour *	Black
Display brightness *	500 cd/m <sup>2</sup>	VESA mounting *	✓
HD type *	4K Ultra HD	Panel mounting interface	600 x 400 mm
Touchscreen *	✗	<b>Performance</b>	
Contrast ratio (typical)	1200:1	On Screen Display (OSD)	✓
Active display area (W x H)	1649.7 x 927.9 mm	Number of OSD languages	26
Panel life	50000 h	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese
<b>Ports &amp; interfaces</b>		<b>Power</b>	
HDMI ports quantity *	3	Power consumption (standby) *	0.5 W
HDMI version	2.0	AC input voltage	100 - 240 V
HDMI input ports quantity	2	AC input frequency	50 - 60 Hz
HDMI output ports quantity	1	<b>Computer system</b>	
DVI port *	✗	Computer system *	✓
VGA (D-Sub) input ports	1	Internal memory	4 GB
DisplayPorts quantity *	1	Internal storage capacity	32 GB
USB port *	✓	Operating system installed	Android 8.0
USB ports quantity	4		
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)		
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	1		
Wi-Fi *	✗		
RS-232 interface	✓		

**Audio**Built-in speaker(s) \* **Weight & dimensions**

Width	1689.5 mm
Depth	91.1 mm
Height	967.7 mm
Weight	52 kg

**Operational conditions**

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 60 °C



4718755081064

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date