## D-Link DGS-1520-28MP verkkokytkin Hallittu L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : D-Link

Tuotekoodi: DGS-1520-28MP



Tuotteen nimi : DGS-1520-28MP

D-Link DGS-1520-28MP. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 20. MAC-osoitetaulukko: 16384 entries, Kytkentäkapasiteetti: 140 Gbit/s. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U

Management features		Security	
Switch type *	Managed	Loop protection	1
Switch layer	L3	BPDU filtering/protection	1
Web-based management	✓	Multicast features	
Ports & interfaces		Multicast Listener Discovery (MLD)	v1/v2
Basic switching RJ-45 Ethernet ports guantity *	20	snooping	V1/V2
Basic switching RJ-45 Ethernet ports		Protocols	
type *	Gigabit Ethernet (10/100/1000)	GARP VLAN Registration Protocol	1
2.5G Ethernet (copper) ports	4	(GVRP) Routing protocols	OSPF, RIP, RIPng, VRRP
quantity 10G Ethernet (copper) ports			
quantity	2	Design	
SFP+ module slots quantity	2	Rack mounting *	
Fiber ports quantity	2	Stackable *	✓ 111
Fiber optic connector	SFP+	Form factor Product colour	1U Black
Network			DIACK
10G support *	1	Performance	_
Flow control support	1	Physical stacking (units)	8 32
Link aggregation	<ul> <li>Image: A set of the set of the</li></ul>	Virtual stacking (units) Noise level	52 57.1 dB
Auto MDI/MDI-X	1	Mean time between failures (MTBF)	
Spanning tree protocol	1	Power	
Head-of-line (HOL) blocking	<ul> <li>Image: A set of the set of the</li></ul>	Power consumption (max)	453.3 W
VLAN support	<ul> <li>Image: A set of the set of the</li></ul>		455.5 W
Data transmission		Power over Ethernet (PoE)	
Switching capacity *	140 Gbit/s	Power over Ethernet (PoE) *	✓
Forwarding rate	104.16 Mpps	Power over Ethernet plus (PoE+) ports quantity	20
MAC address table *	16384 entries	Total Power over Ethernet (PoE)	370 W
Store-and-forward	1	budget	570 W
Static route	1	Operational conditions	
Jumbo frames support	✓	Heat dissipation	1545.8 BTU/h
Jumbo frames	12288	Weight & dimensions	
Security		Weight	4.29 kg
IGMP snooping	✓	Logistics data	
		Harmonized System (HS) code	85176990





790069454776

0790069454776



7900694547764

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.