Vehicle base for the DODGE STRATUS (2005-NEWER)

SPECIFICATIONS

Placement

Passenger side on the floor, under front seat

Drilling Required

No - uses existing seat bolts

Seat Configuration

Bucket

Construction/Finish

Steel/Black Powdercoat

Dimensions

A =16.812" B = 8.875" C = 2" Hole Centers =13.75"

Pole or Pedestal

Purchased Separately

Weight

3.6 lbs.

Features

Installs in minutes with no drilling required Won't interfere with passenger leg space

Misc.

Rock solid construction


Lifetime warranty

RAM Mounting Systems

8410 Dallas Ave S Seattle, WA 98108 Phone: (206) 763-8361 Fax: (206) 763-9615 www.rammount.com support@rammount.com



Shown In Use



RAM-VB-147



RMR-INS-VB-147

RAM No-Drill TM Seat Bases RAM Mounting Systems

Vehicle base for the DODGE STRATUS (2005-NEWER)

INSTALLATION INSTRUCTIONS

- 1. Move the passenger seat back to its rearmost position and remove the front seat rail bolts.
- 2. Without moving the seat, place the No-Drill TM base over the front of the seat frame legs.
- 3. Align the holes in the base with those of the seat frame legs. The pedestal platform should be near the console.
- 4. Re-install the seat bolts and fully tighten.

RAM Mounting Systems

8410 Dallas Ave S Seattle, WA 98108 Phone: (206) 763-8361 Fax: (206) 763-9615 www.rammount.com support@rammount.com



RMR-INS-VB-147