




rammount.com
1.800.497.7479
support@rammount.com

GDS® Hardwire Charger with mUSB Plug and Type-A Port

Install Specifications

- 1 Ensure that the adapter has been installed with power connected to the battery or a constant vehicle power source. Confirm the LED light is on.
- 2 Connect the peripheral (bar code scanner, USB Flash drive, printer, keyboard, mouse, etc.) to the Type-A port before connecting the host device (phone or tablet) to the mUSB connector.
- 3 Plug the USB Micro B cable into phone or tablet.
- 4 Phone or tablet will be now charging from adapter.
- 5 Adapter can be mounted in any location that is not in direct exposure to water.
- 6 Phone or tablet will now be able to use the serial peripheral and charge at the same time.



Tablet Compatibility

This list is not complete, yet contains tablets that have been tested. There might be changes or previous / subsequent modifications made by the OEM to the listed product that might reduce or eliminate compatibility without notice.

- Samsung Galaxy Tab A (8.0", 9.7", 10.1")
- Samsung Galaxy Tab S2 (8.0", 9.7")
- Samsung Galaxy Tab E (8.0") **supports up to SM-T377w**
- Samsung Galaxy Tab 4 (8.0", 10.1")
- Samsung Galaxy Tab S (8.4", 10.5")