

APC APDU9959EU3 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : APC


Product code: APDU9959EU3

Product name : APDU9959EU3

With Industry leading reliability, manageability, and security, APC Switched Rack PDU's provide advanced load management plus on/off outlet level power cycling and sequencing control
Includes: Installation guide, Locking input power cord, Rack mounting brackets, Safety guide Rack PDU 9000 Switched, ZeroU, 16A, 230V, (21) C13 & (3) C19, IEC309 Cord
APC APDU9959EU3. PDU types: Switched, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3 m. Nominal input voltage: 230, 220 - 240 V, Maximum current: 16 A, AC input frequency: 50 - 60 Hz. Certification: EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, RCM, VDE



Design		Power	
/	Switched Single-phase	Maximum total current draw per phase	16 A
Rack capacity *	OU	Maximum power	3680 W
MountingVerticalProduct colourBlackDisplayLCDOn/off switchX	Vertical	Certificates	
	Certification	EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, RCM, VDE	
Ports & interfaces		Operational conditions	
AC outlets quantity * Power plug AC outlet types *	24 AC outlet(s) IEC 60309 C13 coupler, C19 coupler	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 - 45 °C -25 - 65 °C 0 - 95% 5 - 95%
Features		Operating altitude	0 - 3048 m
Daisy chain	✓	Non-operating altitude	0 - 15240 m
Cable length	3 m	Weight & dimensions	
Power		Width	55 mm
ominal input voltage *230, 220 - 240 VC input frequency50 - 60 Hzlaximum current *16 A	Depth Height Weight	46 mm 1794 mm 5.61 kg	
Nominal output voltage	itput voltage 230 V ad capacity 3680 VA	Packaging data	
Output voltage Load capacity Maximum input current per phase		Package weight Package width Package depth Package height	8.59 kg 165 mm 114 mm 2002 mm





731304356295

0731304356295

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.