



APC APDU9959EU3 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : APC

Product code: APDU9959EU3

Product name : APDU9959EU3

- With Industry leading reliability, manageability, and security, APC Switched Rack PDU's provide advanced load management plus on/off outlet level power cycling and sequencing control
 - Includes: Installation guide, Locking input power cord, Rack mounting brackets, Safety guide
 Rack PDU 9000 Switched, ZeroU, 16A, 230V, (21) C13 & (3) C19, IEC309 Cord
 APC APDU9959EU3. PDU types: Switched, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3 m, Certification: EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, RCM, VDE. Nominal input voltage: 230, 220 - 240 V, Maximum current: 16 A, AC input frequency: 50 - 60 Hz. Width: 55 mm, Depth: 46 mm, Height: 1794 mm



Design		Power	
PDU types *	Switched	Maximum input current per phase	16 A
Type	Single-phase	Maximum total current draw per phase	16 A
Rack capacity *	0U	Maximum power	3680 W
Mounting	Vertical	Weight & dimensions	
Product colour	Black	Width	55 mm
Display	LCD	Depth	46 mm
On/off switch	✘	Height	1794 mm
		Weight	5.61 kg
Ports & interfaces		Packaging data	
AC outlets quantity *	24 AC outlet(s)	Package weight	8.59 kg
Power plug	IEC 60309	Package width	165 mm
AC outlet types *	C13 coupler, C19 coupler	Package depth	114 mm
		Package height	2002 mm
Features		Operational conditions	
Daisy chain	✔	Operating temperature (T-T)	-5 - 45 °C
Cable length	3 m	Storage temperature (T-T)	-25 - 65 °C
Certification	EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, RCM, VDE	Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	5 - 95%
		Operating altitude	0 - 3048 m
		Non-operating altitude	0 - 15240 m
Power			
Nominal input voltage *	230, 220 - 240 V		
AC input frequency	50 - 60 Hz		
Maximum current *	16 A		
Nominal output voltage	239 V		
Output voltage	230 V		
Load capacity	3680 VA		



0731304356295



731304356295

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.