D-Link

D-Link AC1300 1267 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki: D-Link Tuotekoodi: DBA-3620P

Tuotteen nimi: AC1300

D-Link AC1300. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1267 Mbit/s. Tietoturva-algoritmit: AES, SSID. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



| Features | | Design | |
|---|---|--|---|
| 2.4 GHz * 5 GHz * 6 GHz * | ✓ ✓ × | Placement * Product colour * International Protection (IP) code | In-wall, Pole White IP55 |
| Maximum data transfer rate * | 1267 Mbit/s | Antenna | |
| Maximum data transfer rate (2.4 GHz) | 400 Mbit/s | Antenna type * Antenna direction type | Internal Omni-directional |
| Maximum data transfer rate (5 GHz) Ethernet LAN data rates Frequency band | 1 867 Mbit/s 10,100,1000 Mbit/s 2.4 - 5 GHz IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE | Antenna gain level (max) Antenna connector type Number of connectors | 5 dBi RP-SMA 2 |
| | | Certificates | |
| Networking standards | 802.11n, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x | Certification | CE Class B FCC Class B UL IC Class B |
| Cabling technology | 10/100/1000Base-T(X) | Weight & dimensions | |
| Flow control support | ✓ | Width | 115 mm |
| Mean time between failures (MTBF) | 1142136 h | Depth | 65.5 mm |
| Security | | Height | 291.9 mm |
| | | , and the second | |
| Security algorithms * | AES, SSID | Weight | 822 g |
| Security algorithms * MAC address filtering | AES, SSID ✓ | , and the second | |
| , , | · | Weight Operational conditions Operating relative humidity (H-H) | 822 g 10 - 90% |
| MAC address filtering | ✓ | Weight Operational conditions Operating relative humidity (H-H) Operating temperature (T-T) | 822 g 10 - 90% -40 - 50 °C |
| MAC address filtering Number of SSID supported | ✓ | Weight Operational conditions Operating relative humidity (H-H) | 822 g 10 - 90% |
| MAC address filtering Number of SSID supported Ports & interfaces | 16 | Weight Operational conditions Operating relative humidity (H-H) Operating temperature (T-T) Storage temperature (T-T) | 822 g 10 - 90% -40 - 50 °C -40 - 65 °C |





790069452901

0790069452901

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.