D-Link

D-Link Nuclias AX3600 2402 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki: D-Link Tuotekoodi: DBA-X2830P

Tuotteen nimi: Nuclias AX3600

D-Link Nuclias AX3600. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 2402 Mbit/s. Tietoturvaalgoritmit: SSID, WPA, WPA-RADIUS, WPA2, WPA3. Ethernet LAN -datanopeudet: 10,100,1000,25000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen. Tehonkulutus (maks.): 27 W





Features		Ports & interfaces	
2.4 GHz *	✓	Internal RJ-45 ports quantity	1
5 GHz *	✓	WAN connection	Ethernet (RJ-45)
Maximum data transfer rate *	2402 Mbit/s	Power	
Maximum data transfer rate (2.4 GHz)	1147 Mbit/s	Power over Ethernet (PoE) *	✓
Maximum data transfer rate (5 GHz)	2402 Mbit/s	Output voltage	12 V
Ethernet LAN data rates	10,100,1000,25000 Mbit/s	Output current	2.5 A
Throughput data rate	3.6 Mbit/s	Power consumption (typical)	25.1 W
	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ab, IEEE 802.3at, IEEE	Power consumption (max)	27 W
Networking standards		Design	
		Placement *	Ceiling, Table, Wall
	802.3az, IEEE 802.3i, IEEE 802.3u,	Product colour *	White
	IEEE 802.3x	On/off switch	✓
MIMO		Reset button	✓
MIMO type	Multi User MIMO	LED indicators	LAN, PoE, Power
VLAN support	1	Antenna	
Flow control support	✓		
Band steering	✓	Antenna type *	Internal
Transmitting power (CE)	20 dBm	Antenna direction type	Omni-directional
Transmitting power (FCC)	20 dBm	Antennas quantity	4
Mean time between failures (MTBF)	485000 h	Antenna gain level (max)	4 dBi
Security		Certificates	
Security algorithms *	SSID, WPA, WPA-RADIUS, WPA2, WPA3	Certification	CE Class B FCC Class B UL-2043 IC Class B
MAC address filtering	✓	Weight & dimensions	
IP address filtering	/	Width	224.5 mm
Number of SSID supported	16	Depth	223.9 mm
	-	Height	50 mm

Security		Weight & dimensions	
System status alarm	✓	Weight	935 g
Remote Authentication Dial-In User Service (RADIUS)	✓	Operational conditions	
Service (NADIOS)		Operating relative humidity (H-H)	10 - 90%
Protocols		Operating temperature (T-T)	0 - 40 °C
IPv4 & IPv6 features	IPv6 portal	Storage temperature (T-T)	-20 - 65 °C
Management features		Storage relative humidity (H-H)	5 - 95%
Web-based management	✓	Logistics data	
Firmware upgradeable	✓	Harmonized System (HS) code	85176990
Ports & interfaces			
Ethernet LAN (RI-45) ports *	2		





790069454523

0790069454523

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.