PHILIPS

Philips P Line 326P1H/00 LED display 80 cm (31.5") 2560 x 1440 pixels Quad HD Black

Brand : Philips Product family: P Line Product code: 326P1H/00

Product name: 326P1H/00

- P Line

- 32 (31.5"/80 cm diag.) - 2560 x 1440 (QHD)

Brilliance 326P1H LCD monitor with USB-C docking

Philips P Line 326P1H/00 LED display 80 cm (31.5") 2560 x 1440 pixels Quad HD Black:

The Philips USB-C docking display for a comprehensive solution. View QHD and re-charge a laptop up to 90 W, all at the same time with a single USB-C cable. Pop-up webcam with Windows Hello and daisy-chaining deliver performance and convenience

Philips P Line 326P1H/00. Display diagonal: 80 cm (31.5"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



	Ergonomics	
80 cm (31.5") 2560 x 1440 pixels Quad HD 16:9 LED IPS W-LED X 350 cd/m² 4 ms ✓ Flat 2560 x 1440 16:9 1000:1 50000000:1 SmartContrast 75 Hz 178°	Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD) On Screen Display (OSD) languages Number of OSD languages Plug and Play	100 x 100 mm Kensington 18 cm -90 - 90° -180 - 180° Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian 21
178°	LED indicators	Operation, Stand-by
	Power	
0.2727 x 0.2727 mm 93 ppi san range 30 - 114 kHz range 48 - 75 Hz e, horizontal 69.8 cm e, vertical 39.3 cm ontal frequency 30 - 114 kHz	Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (PowerSave) AC input voltage	G 39 kWh 25.3 W 0.3 W 24 W 100 - 240 V
	2560 x 1440 pixels Quad HD 16:9 LED IPS W-LED X 350 cd/m² 4 ms ✓ Flat 2560 x 1440 16:9 1000:1 50000000:1 SmartContrast 75 Hz 178° 178° 1.07 billion colours 0.2727 x 0.2727 mm 93 ppi 30 - 114 kHz 48 - 75 Hz 69.8 cm 39.3 cm	80 cm (31.5") Panel mounting interface 2560 x 1440 pixels Quad HD Cable lock slot * Quad HD Cable lock slot type 16:9 Height adjustment * LED Height adjustment IPS Pivot Pivot angle Swivelling 350 cd/m² Swivel angle range Tilt adjustment Ilt angle range On Screen Display (OSD) SmartContrast 75 Hz Number of OSD languages 1.07 billion colours 0.2727 x 0.2727 mm Panel mounting interface Cable lock slot * Cable lock slot * Cable lock slot * Height adjustment * Height adjustment Pivot Swivel angle Swivel angle range On Screen Display (OSD) On Screen Display (OSD) SmartContrast Number of OSD languages Plug and Play LED indicators Power 1.07 billion colours 0.2727 x 0.2727 mm Power Snergy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Energy consumption (typical) * Power consumption (typical) * Power consumption (PowerSave)

Display		Power	
Digital vertical frequency	48 - 75 Hz	AC input frequency	50 - 60 Hz
Display diagonal (metric)	80 cm	Power supply type	Internal
DDC/CI	✓	Energy efficiency scale	A to G
Haze rate	25%	European Product Registry for Energy Labelling (EPREL) code	398293
Surface hardness	3H		
Colour gamut standard	sRGB	Operational conditions	
Colour gamut	89%	Operating temperature (T-T)	0 - 40 °C
sRGB coverage (typical)	118%	Storage temperature (T-T)	-20 - 60 °C
NTSC coverage (typical)	106%	Operating relative humidity (H-H)	20 - 80%
Adobe RGB coverage	87%	Operating altitude	0 - 3658 m
Display sRGB	✓	Non-operating altitude	0 - 12192 m
Performance		Weight & dimensions	
Component video sync	Separate sync	Width (with stand)	714 mm
Flicker-free technology	✓	Depth (with stand)	280 mm
Low Blue Light technology	✓	Height (with stand)	649 mm
Multimedia		Weight (with stand)	12.2 kg
Number of speakers	2	Width (without stand)	714 mm 62 mm
RMS rated power	10 W	Depth (without stand) Height (without stand)	62 mm 422 mm
Built-in speaker(s) *	✓	Weight (without stand)	8.21 kg
Megapixel (approx.)	2 MP		O'LI NY
Built-in microphone	✓ · · · ·	Packaging data	
Built-in camera *	·	Package width	930 mm
	•	Package depth	186 mm
Design		Package height	563 mm
Market positioning *	Home	Package weight	15.5 kg
Product colour *	Black	Package type	Вох
Front bezel colour	Black	Packaging content	
Detachable stand	•	Stand included	✓
Feet colour	Black	Cables included	HDMI, DisplayPort, USB Type-C, AC
Ports & interfaces		Manual	✓
Built-in USB hub *	✓	Bundled software	SmartControl
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability	
USB upstream port type	USB Type-C	Sustainability certificates	ENERGY STAR, TCO
Number of upstream ports	1	Doesn't contain	Mercury, PVC/BFR
Number of USB Type-C upstream ports quantity	1	Other features	
USB Type-A downstream ports	4	HBR3 support	✓
quantity		USB Power Delivery revision	3.0
USB Type-C DisplayPort Alternate Mode	✓	Exterior finish type	Textured
USB Power Delivery (USB PD)	✓	Recyclable packaging material	100%
USB Power Delivery up to	90 W	Heavy metals free	Hg (mercury), Pb (lead)
DVI port	×	Light sensor	•
HDMI*	1	EasyRead mode	✓
HDMI ports quantity	2	LowBlue mode	✓
HDMI version	1.4	Philips SmartUniformity	93 - 105%
DisplayPorts quantity	2	Picture enhancement	SmartImage
DisplayPort version	1.4		CB; TUV/GS; TUV Ergo; SEMKO; CU-
Audio input	×	Regulatory Approvals	EAC; EAEU RoHS; CCC; CEL; CECP; CE Mark; FCC Class B; ICES-003;
Audio output	✓		TUV Eye Comfort certified
Headphone out *	×	Delta E	2
HDCP	^ /	Compliance certificates	RoHS
HDCP version	2.2	Mean time between failures (MTBF)	70000 h
Charging port type	USB Type-C + USB Type-A	Ethernet LAN data rates	10,100,1000 Mbit/s
AC (power) in	✓	Wake-on-LAN	✓
DisplayPort output	·	Certification	CB, TUV/GS, TUV Ergo, SEMKO, CU- EAC, EAEU RoHS, CCC, CEL, CECP, CE Mark, FCC Class B, ICES-003,
			TUV Eye Comfort certified

Network		Recycling data	
Ethernet LAN	✓	Post-consumer recycled plastic	85%
Ergonomics		Logistics data	
VESA mounting *	✓	Harmonized System (HS) code	85285210



8712581768096

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.