

## BenQ W5700 data projector Standard throw projector 1800 ANSI lumens DLP UHD 4K (3840x2160) Black

**Brand :** BenQ **Product code:** 9H.JKV77.1HE

**Product name:** W5700

- True 4K UHD resolution with 8.3M pixels
- BenQ CinematicColor™ for cinema industry's 100% DCI-P3/Rec.709 color space
- HDR-PRO™ projector-optimized HDR technology (HDR10/HLG support)

DLP, 3840x2160, 1800 lum, 60-200/300", HDMI, USB, LAN, RS-232, DC 12V, IR, HDR, 100-240V AC, 492x168x349 mm

BenQ W5700. Projector brightness: 1800 ANSI lumens, Projection technology: DLP, Projector native resolution: UHD 4K (3840x2160). Light source type: Lamp, Service life of light source: 4000 h, Service life of light source (economic mode): 10000 h. Focus: Manual, Focal length range: 14.3 - 22.9 mm, Aperture range (F-F): 1.81 - 2.1. Supported graphics resolutions:  $640 \times 480$  (VGA),  $720 \times 400$ ,  $800 \times 600$  (SVGA),  $832 \times 624$ ,  $1024 \times 576$  (WSVGA),  $1024 \times 768$  (XGA),..., Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080p, 2160p. Serial interface type: RS-232, HDMI connector type: Full-size, HDMI version: 2.0b





Dura la atra u		Material	
Projector		Network	
	16:9 1524 - 7620 mm (60 - 300")	Smart TV *	X
Projection distance	1.75 - 9.32 m	Ethernet LAN *	<b>✓</b>
Contrast ratio (dynamic)	100000:1	Ethernet LAN (RJ-45) ports	1
Projector brightness *	1800 ANSI lumens	Wi-Fi *	×
Projection technology *	DLP	Storage	
Projector native resolution *	UHD 4K (3840x2160)	Card reader integrated *	×
Native aspect ratio * 16:9	16:9 1.073 billion colours	Features	
Number of colours Horizontal scan range	1.073 billion colours 15 - 102 kHz	Noise level (economic mode)	26 dB
Vertical scan range	23 - 120 Hz	HDCP	✓
Keystone correction, vertical	-40 - 40°	On Screen Display (OSD)	1
Light source Light source type * Service life of light source * Service life of light source	Lamp 4000 h	On Screen Display (OSD) languages	Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish
(economic mode) Lamp power	10000 h 245 W		
Lens system		Number of OSD languages	28
Focus *	Manual	Noise level *	32 dB
Focal length range	14.3 - 22.9 mm	Multimedia	
Aperture range (F-F)	1.81 - 2.1	Built-in speaker(s) *	×
Zoom capability	<b>/</b>		
Zoom ratio	1.6:1	Design	
Throw ratio Horizontal lens shift range	1.36 - 2.18 -23 - 23%	Market positioning *	Home cinema
Vertical lens shift range	-23 - 23% -60 - 60%	Product type *	Standard throw projector
vertical lens still range	-00 - 0070	Product colour *	Black
		Placement	Desktop, Ceiling

Video		Display	
Full HD *	✓	Built-in display *	×
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 832 x 624, 1024 x 576 (WSVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1152 x 870, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 1360 x 768 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA),	Power	
		Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input voltage	AC 330 W 0.5 W 405 W 247 W 100 - 240 V
Supported video modes	3840 x 2160 480i, 480p, 576i, 576p, 720p,	Operational conditions	
Ports & interfaces	1080p, 2160p	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
HDMI connector type HDMI version USB 2.0 ports quantity *	Full-size 2.0b 2	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	10 - 90% 10 - 90% 0 - 1499 m
Mini-USB 2.0 ports quantity	1	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Serial interface type * PC Audio out HDMI ports quantity *	1 RS-232 ✓	Width Depth Height Weight *	492 mm 349 mm 168 mm 6.5 kg
DVI port *	X	Packaging content	
Mobile High-Definition Link (MHL) AC (power) in DC-in jack	×	Remote control included * Cables included Manual	✓ AC ✓
		Logistics data	
		Harmonized System (HS) code	85286200

