

## APC EPDU1232S power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : APC Product code: EPDU1232S

**Product name:** EPDU1232S

EasyPDU, Switched, Zero U, 22 kW, 230V, 18 x C13 & 6 x C19

APC EPDU1232S power distribution unit (PDU) 24 AC outlet(s) 0U Black:

Easy Switched Rack Power Distribution Units (Rack PDU) provide on/off outlet switching, advanced power management, load monitoring and much more features than the average power strip.

APC EPDU1232S. PDU types: Switched, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 2 m, Certification: EAC, RCM, TÜV. Nominal input voltage: 400 V, Maximum current: 32 A, AC input frequency: 50 - 60 Hz. Width: 55 mm, Depth: 62 mm, Height: 1794 mm





| Design   |  | Weight & dimensions                                       |  |
|--|--|---|--|
| PDU types * Rack capacity * Mounting                                     | Switched<br>0U<br>Vertical                         | Depth<br>Height<br>Weight                                 | 62 mm<br>1794 mm<br>8.17 kg            |
| Product colour   | Black  | Packaging data  |  |
| Ports & interfaces  AC outlets quantity *  Power plug  AC outlet types * | 24 AC outlet(s) IEC 60309 C13 coupler, C19 coupler | Package weight Package width Package depth Package height | 9.45 kg<br>160 mm<br>110 mm<br>1950 mm |
| Features   |  | Operational conditions                                    |  |
| Cable length<br>Certification  | 2 m<br>EAC, RCM, TÜV                               | Operating temperature (T-T) Storage temperature (T-T)     | -5 - 45 °C<br>-25 - 65 °C              |
| Power  |  | Operating relative humidity (H-H)                         | 5 - 95%                                |
| Nominal input voltage * AC input frequency                               | 400 V<br>50 - 60 Hz                                | Storage relative humidity (H-H) Operating altitude        | 5 - 95%<br>0 - 3000 m                  |
| Maximum current *  | 32 A   | Technical details   |  |
| Output voltage<br>Maximum power  | 230 V<br>22000 W                                   | Sustainability compliance<br>Compliance certificates      | ✓<br>CE                                |
| Weight & dimensions  |  |   |  |
| Width  | 55 mm  |   |  |





731304428039

0731304428039

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.