



# KRAMER

## C-D9F/OPEN

RS-232 to Open End Control Cable

---



Kramer's C-D9F/OPEN control cables are for RS-232 applications to control devices within a professional AV system. Many Kramer products are RS-232 controllable and equipped with terminal block connector. This RS-232 cable helps to connect them safely to transmit the RS-232 serial commands to a touch-screen system, PC, or other serial controller equipped with D9 connector

## FEATURES

---

**Quality Construction** - Constructed using three 28AWG isolated conductors, terminated with a molded female 9-pin D-sub connector, nickel plated on one side and open end, non-terminated, on the second side

**Pinout** - Wired pin to pin on pins 2, 3 & 5

**Molded Strain Relief**

**Stripped & Tinned Wires** - At open end

**RoHS Compliant**

**Varied Selection of Lengths** - 3 to 50ft (1 to 15m)



# KRAMER

## TECHNICAL SPECIFICATIONS

---

Pinout                      Red – pin 2;Green – pin 3;Black – pin 5

CONDUCTORS              Material Tinned Copper

3-10ft (0.9-3m) lengths 28AWG

15-50ft (4.6 -15.2m) lengths 24AWG



# KRAMER

## CONFIGURATIONS

---

|               |                                 |
|---------------|---------------------------------|
| C-D9F/OPEN-3  | RS-232, D9(F) to bare end cable |
| C-D9F/OPEN-6  | RS-232, D9(F) to bare end cable |
| C-D9F/OPEN-10 | RS-232, D9(F) to bare end cable |
| C-D9F/OPEN-15 | RS-232, D9(F) to bare end cable |
| C-D9F/OPEN-25 | RS-232, D9(F) to bare end cable |
| C-D9F/OPEN-35 | RS-232, D9(F) to bare end cable |
| C-D9F/OPEN-50 | RS-232, D9(F) to bare end cable |