

TBUS-1N

Table Mount Modular MultiConnection Solution Retractable Lid



TBUS1N is a modular furnituremounted connection bus enclosure that easily installs into a table or podium top. Once assembled, TBUS1N enables you to connect any equipment to the room's presentation system via cable access or passive interfaces. When the cables are not in use, they can be stored inside the unit, covered by the lid and out of sight.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately

FEATURES

Modular Design - Tailors to your requirements

Cover - Black sandblast or silver sandblast anodized aluminum lid with a special opening for cable passthrough. (Note, other customized colors can be ordered)

Height Adjustment - Use screw holes to set the inner frame (ordered separately) to the desired height

Power Sockets - Single or dual power socket openings are suitable for any of the following power sockets: USA, UK, Switzerland, Germany (the Europlug), BelgiumFrance, Italy, Australia, Israel, Brazil, South Africa or "Universal" for use anywhere

Cutout Dimensions - 195 +2mm x 173 +2mm (7.68 +0.08in x 6.82 +0.08in)



TECHNICAL SPECIFICATIONS

COLOR: Black and silver sandblasted finish

POWER SOURCE: Single socket: 100240V AC 50/60Hz, 5A (Universal, USA, Germany and EU,

Belgium and France, Italy, Australia) or 220V AC 50/60Hz, 5A (Israel, South

Africa).

Dual power kit assemblies: 100240V AC 50/60Hz, 5A (Universal, USA, Germany

and EU, France) or 220V AC 50/60Hz, 5A (Israel, South Africa)

FUSE RATING: T 6.3A 250V

OPERATING TEMPERATURE:

0° to +40°C (32° to 104°F)

STORAGE

40° to +70°C (40° to 158°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL noncondensing

STORAGE HUMIDITY 5 to 95% RHL, noncondensing

RANGE:

DIMENSIONS: 21.4cm x 19.2cm x 13.6cm (8.42" x 7.56" x 5.35") W, D, H

WEIGHT: TBUS1N: 2kg (4.4lbs) approx.; accessories (table clamps, metal template and so

on): 0.89kg (1.96lbs)

ACCESSORIES: Six selflocking ties, metal template

OPTIONS: Inner frames, passive wall plates and interfaces, power socket kits, power cord



CONFIGURATIONS

TBUS-1N(B)	Enclosure — Black Sand Blasted Anodized Aluminum Top
TBUS-1N(BC)	Enclosure — Silver Sand Blasted Anodized Aluminum Top
TBUS-1N(BA)	Enclosure - Brushed Clear Anodized Aluminum Top

