## QNAP

## QNAP TS-H973AX NAS Tower Ryzen Embedded V1500B 32 GB DDR4 0 TB QuTS hero musta

Tuotemerkki : QNAP Tuotekoodi: TS-H973AX-32G

**Tuotteen nimi :** TS-H973AX

QNAP TS-H973AX. Malli: NAS. Alustatyyppi: Tower. Laitteen luokka: Pienet & Keskikokoiset Yritykset. Suoritinperhe: Ryzen Embedded, Prosessorimalli: V1500B, Prosessorin taajuus: 2,2 GHz. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4. Asennetun muistin kokonaiskapasiteetti: 0 TB. Käyttöjärjestelmä asennettu: QuTS hero





Storage		
	Design	
Storage drive capacity * 0 GB	Cable lock slot type	Kensington
Supported storage drive interfaces Serial ATA II, Serial ATA	Performance	
Storage drive sizes supported  RAID support *  RAID levels  Online RAID expansion  RAID rebuild  Hot-swap drive bays  Supported file systems  Storage drives installed *  Total installed storage drives supported  *  Installed storage drive type *  Supported storage drive types *  Supported storage drive types *  Supported storage drive types *  Long Storage drive sizes supported 2.5, 3.5"  A	Backup function **  Backup features  Buzzer  Multilingual support  S, exFAT,  Noise level  Third-party support  Snapshot  Security algorithms  Access Control List (ACL)  Reset button	NAS Small & Medium Business  Cloud, iSCSI LUN  22.9 dB  256-bit AES, HTTPS, SSH
Disk roaming	On/off switch  Built-in FTP server	<b>/</b>
Processor  Processor manufacturer * AMD  Processor generation AMD Ryzen Embedded Norcessor family * Ryzen Embedded  Processor model * V1500B  Processor frequency * 2.2 GHz  Processor cores 4  Processor threads 8	Browser supported	Apple Safari, Google Chrome, Microsoft Internet Explorer, Mozilla Firefox
Memory	Share folder	AFP, CIFS/SMB, FTP, WebDAV
	USB copy function	✓
·		
•	Software	
Internal memory * 32 GB Internal memory type DDR4 Maximum RAM supported 32 GB Memory slots 2	Software Operating system installed * Operating system version	QuTS hero h5.0.0
Internal memory * 32 GB Internal memory type DDR4 Maximum RAM supported 32 GB Memory slots 2 Memory form factor SO-DIMM	Operating system installed *	,

Network		Software	
Ethernet LAN data rates	100,1000,2500,5000,10000 Mbit/s		Windows 10, Windows 10
Ethernet LAN data rate supported (max) Copper ethernet cabling technology		X64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 10 Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Windows 7 Enterprise, Windows 7 Windows 7 Home Basic x6 Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Professional, Windows Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7	Windows 10 Enterprise x64, Windows 10 Home, Windows 10
DHCP client DHCP server	✓ ✓		Windows 10 Pro, Windows 10 Pro
Jumbo frames support	<b>√</b>		x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7.
iSCSI support	·		Windows 7 Enterprise, Windows 7
Wake-on-LAN ready	· ✓		Basic, Windows 7 Home Basic x64,
Supported network protocols	IPv4, IPv6		•
Link aggregation	✓		Windows 7 Professional, Windows 7
Load balancing system	✓		
Dynamic DNS (DDNS)	✓		Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64,
Ports & interfaces			Windows 8, Windows 8 Enterprise,
USB port *	✓		Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	3	8 x64	8 x64 CentOS 7.0, SuSE Linux 12.0, SuSE
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1		Linux 12.3, SuSE Linux 15, Ubuntu 14.04, Ubuntu 14.10, Ubuntu 15.04,
Ethernet LAN (RJ-45) ports *	3	Linux operating systems supported	Ubuntu 15.10, Ubuntu 16.04,
Concurrent connections	2000		Ubuntu 16.10, Ubuntu 17.10, Ubuntu 18.04 LTS, Ubuntu 20.04
Design			LTS
Chassis type *	Tower		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Cooling type *	Active		Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X
Product colour Number of fans	Black 1 fan(s)	Mac operating systems supported	10.15 Catalina, Mac OS X 10.15.3
Fan diameter	14 cm		Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X
Drive bay locking	<b>✓</b>		10.9 Mavericks, Mac OS X 11.0 Big Sur
LED indicators	HDD, LAN, Power, SSD, Status, USB		
	,,,,,		Windows Server 2003, Windows
Cable lock slot	✓	Server operating systems supported	Server 2008 R2, Windows Server
		Server operating systems supported  Other operating systems supported	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
			Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10,
		Other operating systems supported	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10,
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11 External 120 W
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W 41.2 W
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W 41.2 W 100 - 240 V
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *  Weight	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V  224.6 mm 224.1 mm 182.7 mm 3.52 kg
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *  Weight  Package weight	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 55.41 W 41.2 W 100 - 240 V 12 V  224.6 mm 224.1 mm 182.7 mm 3.52 kg
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *  Weight  Package weight  Packaging content  External power adapter  Cables included	Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1 1 55.41 W 41.2 W 100 - 240 V 12 V   224.6 mm 224.1 mm 182.7 mm 3.52 kg 5.12 kg
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *  Weight  Package weight  Packaging content  External power adapter  Cables included  Power cables quantity	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *  Weight  Package weight  Packaging content  External power adapter  Cables included  Power cables quantity  Quick installation guide	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1
		Other operating systems supported  Power  Power supply location  Power supply unit (PSU) capacity  Number of power supply units  Power consumption (typical)  Power consumption (HDD standby)  AC input voltage  Fan voltage  Weight & dimensions  Width *  Depth *  Height *  Weight  Package weight  Packaging content  External power adapter  Cables included  Power cables quantity	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11  External 120 W 1

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-20 - 70 °C
Storage relative humidity (H-H)	5 - 95%
Logistics data	
Harmonized System (HS) code	84714100



4713213518663

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.