LG

LG 49XS4J-B Digital signage display 124.5 cm (49') Wi-Fi 4000 cd/m² Full HD Black Web OS 24/7

Brand : LG

Product code: 49XS4J-B

Product name : 49XS4J-B Digital signage display 124.5 cm (49') Wi-Fi 4000 cd/m² Full HD Black Web OS 24/7

- Brightness : 4,000 nits (Typ.) / 3,200 nits (Min.)
- Resolution : Full HD (1,920 x 1,080)
- Bezel (T,B / R,L) : 9.0 / 6.5 mm
- webOS-based High Performance
- Built-in Wi-Fi
- Web-based Monitoring Solution
49", 1920 x 1080 Full HD, IPS, 16GB, 60 Hz, Wi-Fi, 8ms, WebOS, HDMI, RS232C, RJ45, USB
LG 49XS4J-B Digital signage display 124.5 cm (49') Wi-Fi 4000 cd/m² Full HD Black Web OS 24/7. Product design: Digital signage flat panel. Display diagonal: 124.5 cm (49"), Display resolution: 1920 x 1080 pixels, Display brightness: 4000 cd/m², HD type: Full HD. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: WebOS. Product colour: Black

CE

Display

Panel type	IPS
LED backlighting type	Direct-LED
Display diagonal *	124.5 cm (49")
Display resolution *	1920 x 1080 pixels
Display brightness *	4000 cd/m²
HD type *	Full HD
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1300:1
Contrast ratio (dynamic)	500000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Rated lifetime	50000 h
Native refresh rate	60 Hz
Haze rate	3%

Ports & interfaces

HDMI ports quantity *	2
HDMI version	1.4
HDMI input ports quantity	2
DisplayPorts quantity *	2
DisplayPorts in	1
DisplayPorts out	1
USB port *	✔
USB ports quantity	1
USB version	2.0
Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✔
Number of speaker outputs	2
RS-232 interface	✔
RS-232C	✔
Remote (IR) input	1

Design

Product design *	Digital signage flat panel

Design

Mounting type	Wall

Performance

Purpose *	Commercial
Multi-display supported	✔
On Screen Display (OSD)	✔
Number of OSD languages	21
On Screen Display (OSD) languages	Turkish
Ambient light sensor	✔
Operating hours (hours/days)	24/7

Power

Power consumption (typical) *	345 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Heat dissipation	117 BTU/h

Computer system

Internal memory	16 GB
Operating system installed	WebOS

Weight & dimensions

Display width	1092.7 mm
Display depth	83.5 mm
Display height	626.4 mm
Display weight	20.8 kg

Packaging data

Package width	1181 mm
Package depth	725 mm
Package height	212 mm
Package weight	25.3 kg

Packaging content

Remote control included	✔
Batteries included	✔
Cables included	AC

Design

Placement supported *	Indoor/outdoor
Orientation	Horizontal/Vertical
Product colour *	Black
VESA mounting *	✓
Panel mounting interface	600 x 400 mm
Bezel width (bottom)	9 mm
Bezel width (side)	6.5 mm
Bezel width (top)	9 mm

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%

Logistics data

Harmonized System (HS) code	85285210

Features

Heat dissipation (max)	1262 BTU/h

Technical details

Sustainability certificates	ErP
Compliance certificates	CE

0195174012178

195174012178

8806091355027

5715063337394