Verbatim Vi550 S3 SSD 512GB

Brand : Verbatim

Product name : Vi550 S3 SSD 512GB

Product code: 49352

Vi550 Internal SATA III 2.5'' SSD 512GB

Verbatim Vi550 S3 SSD 512GB:

Verbatim 2.5'' SATA III 7mm solid state drives can revitalise the performance of your system. Using the latest 3D NAND technology they offer the perfect way to upgrade from either hard drive or an older SSD. The Vi550 has a superior controller for increased reliability, larger capacities and faster read/write speeds.

Expand the lifetime of your laptop or PC
Breathe new life into an older system by replacing a tired hard drive or a legacy 2D NAND SSD with a Vi550 S3 SSD. The Vi550 offers read speeds of up to 560MB/s, up to 20 times faster than a standard hard drive. With a MTBF (mean time before failure) rating of 2 million hours and TBW rating of up to 480TB (1TB capacity), the Vi550 is a high spec SSD that can be relied upon. Recommended for professional installation.
Verbatim Vi550 S3 SSD 512GB. SSD capacity: 512 GB, SSD form factor: 2.5", Read speed: 520 MB/s, Write speed: 500 MB/s, Data transfer rate: 6 Gbit/s, Component for: PC/Laptop

Features

SSD capacity *	512 GB
SSD form factor *	2.5"
Interface *	Serial ATA III
NVMe *	✘
Memory type *	3D NAND
Component for *	PC/Laptop
Hardware encryption *	✘
Data transfer rate	6 Gbit/s
Read speed	520 MB/s
Write speed	500 MB/s
Mean time between failures (MTBF)	2000000 h
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	✔
TBW rating	360
SSD usage tag	Consumer

Weight & dimensions

Width	69.9 mm
Depth	100.5 mm
Height	7 mm
Weight	45 g

Packaging data

Quick start guide	✔
Package width	109 mm
Package depth	24 mm
Package height	159 mm
Package weight	62 g
Package type	Blister

Operational conditions

Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating shock	1500 G
Vibration resistance	20 G

Other features

Compliance certificates	RoHS

Logistics data

Master (outer) cases per pallet	780 pc(s)
Layers per pallet	6 pc(s)
Products per pallet	1560 pc(s)
Master (outer) case width	168 mm
Master (outer) case length	115 mm
Harmonized System (HS) code	84717070
Master (outer) case height	58 mm
Master (outer) case gross weight	163 g
Products per master (outer) case	2 pc(s)

0023942493525

023942493525