



## DELL WD19S-180W Langallinen USB 3.2 Gen 2 (3.1 Gen 2) Type-C musta

**Tuotemerkki :** DELL

**Tuotekoodi:** DELL-WD19S180W

**Tuotteen nimi :** WD19S-180W

DELL WD19S-180W. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 2 (3.1 Gen 2) Type-C. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Tuotteen väri: musta, Digitaalinen enimmäistarkkuus: 5120 x 2880 pikseliä. Virtalähteen malli: DC, AC-syöttöjännite: 120 - 230 V, AC-syöttötaajuus: 50 - 60 Hz. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10...



Ports & interfaces		Power	
Connectivity technology *	Wired	AC input frequency	50 - 60 Hz
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C	Power supply	180 W
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3	Power cable length	1 m
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	<b>Software</b>	
HDMI ports quantity *	1	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64
HDMI version	2.0	Linux operating systems supported	✓
DisplayPorts quantity	2	<b>Operational conditions</b>	
DisplayPort version	1.4	Operating temperature (T-T)	0 - 35 °C
Microphone in *	✗	Storage temperature (T-T)	-20 - 60 °C
DC-in jack	✓	Operating relative humidity (H-H)	10 - 80%
<b>Network</b>		Storage relative humidity (H-H)	5 - 90%
Ethernet LAN *	✓	<b>Weight &amp; dimensions</b>	
Ethernet LAN (RJ-45) ports	1	Width	205 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Depth	90 mm
<b>Performance</b>		Height	29 mm
Card reader integrated *	✗	Weight	585 g
Maximum digital resolution	5120 x 2880 pixels	<b>Packaging data</b>	
VESA mounting	✓	Quantity per pack	1 pc(s)
Product colour *	Black	Package width	300 mm
On/off switch	✓	Package depth	290 mm
LED indicators	✓	Package height	62 mm
<b>Power</b>			
Power source type	DC		
AC input voltage	120 - 230 V		

**Logistics data**


Harmonized System (HS) code 84733020



5397184513989



5704174402169



5055190199428



5704174575382



5704174558521



0884116398349



884116398349

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.