



Galil 4-CO

4-Inch, 2-Way Open-Back Ceiling Speakers

| Speakers



The Galil 4-CO is a pair of two-way, open-back, 8 Ω speakers designed for mounting in the ceiling. The speakers feature a multi-tap power transformer for selecting 8 Ω or 70V/100V power settings suitable for array installation

FEATURES

Type - 2-way coaxial speaker

Woofer - 4" polypropylene cone

Tweeter - 0.5" Mylar dome

Frequency Response - 80Hz to 20kHz@ \pm 3dB

Impedance - 8 Ω

Power Handling - 15W RMS, 40W continuous program

Transformer Taps - 70V: 15W/7.5W/3.7W/Off (Lo-Z); 100V: 15W/7.5W/Off (Lo-Z)

Package Includes - 2 speakers (1 pair), cutout template and user manual

Mounting Bracket (Optional) - SKIC-4



KRAMER

TECHNICAL SPECIFICATIONS

DESCRIPTION:	2-way open-back ceiling speakers
FREQUENCY RESPONSE:	60Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB
WOOFER:	4" (103mm) polypropylene with rubber surround
TWEETER:	0.5" (13mm) Mylar
IMPEDANCE:	8Ω (transformer tap in off position)
TRANSFORMER TAPS:	70V-15W/7.5W/3.7W/Off (Lo-Z), 100V-15W/7.5W/Off (Lo-Z)
SENSITIVITY:	83dB SPL, 1W@1m
MAX SPL:	Continuous: 95dB; peak: 98dB
POWER HANDLING:	15W RMS, 40W continuous program
CROSSOVER FREQUENCY:	13kHz
COVERAGE ANGLE:	104°
DIRECTIVITY FACTOR (Q):	8 averaged 1kHz to 10kHz
DIRECTIVITY INDEX (DI):	9dB averaged 1kHz to 10kHz
INPUT CONNECTOR:	Terminal block
MATERIALS:	Frame, aluminum grill, safety cord attached to grill
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
WEIGHT PER SINGLE SPEAKER:	0.95kg (2.09lbs) approx
SHIPPING WEIGHT (FOR PAIR):	2.6kg (5.73lbs) approx
INSTALLATION CLEARANCE:	Mounting depth: 6.82cm (2.7")
CUTOUT DIAMETER	13.9cm (5.47")
OPTIONAL ACCESSORIES:	SKIC-4 installation bracket
COLORS:	Available in white