



# kramer

## Galil 4-C

4-Inch, 2-Way Closed-Back Ceiling  
Speakers

| Speakers



The Galil 4-C Closed-back Compact Ceiling Speaker features a multi-tap power transformer for selecting 8Ω (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation. The Galil 4-CO open-back version is also available

### FEATURES

Type - 2-way coaxial speaker

Woofers - 4" polypropylene cone

Tweeter - 0.5" Mylar dome

Impedance - 8Ω

Power Handling - 30W RMS, 80W continuous program

Transformer Taps - 70V: 30W/15W/7.5W/3.7W/Off (Lo-Z); 100V: 30W/15W/7.5W/Off (Lo-Z)

UL 1480 & 2043 Listed

Package Includes - 2 speakers (1 pair), ceiling mounting kit, template and user manual

Installation Dimensions - External diameter: 19.5cm (7.68"); cutout diameter: 16.7cm (6.57")



# kramer

## TECHNICAL SPECIFICATIONS

---

|                             |   |
|-----------------------------|---|
| DESCRIPTION:                | 2-way closed-back ceiling speakers  |
| FREQUENCY RESPONSE:         | 85Hz to 20kHz @-10dB, 100Hz to 20kHz @±3dB  |
| WOOFER:                     | 4" (103mm) polypropylene with rubber surround   |
| TWEETER:                    | 0.5" (13mm) Mylar   |
| IMPEDANCE:                  | 8Ω (transformer tap in off position)  |
| TRANSFORMER TAPS:           | 70V – 30W/15W/7.5W/3.7W/Off (Lo-Z), 100V – 30W/15W/7.5W/Off (Lo-Z)                                    |
| SENSITIVITY:                | 85dB SPL, 1W@1m   |
| MAX SPL:                    | Continuous: 95dB, peak: 97dB  |
| POWER HANDLING:             | 30W RMS, 80W continuous program   |
| CROSSOVER FREQUENCY:        | 6kHz  |
| COVERAGE ANGLE:             | 90°   |
| DIRECTIVITY FACTOR (Q):     | 4.2 averaged 1kHz to 10kHz  |
| DIRECTIVITY INDEX (DI):     | 6.2dB averaged 1kHz to 10kHz  |
| INPUT CONNECTOR:            | Terminal block  |
| MATERIALS:                  | ABS bezel, aluminum grill, metal back can   |
| OPERATING TEMPERATURE:      | 0° to +40°C (32° to 104°F)  |
| STORAGE TEMPERATURE:        | -40° to +70°C (-40° to 158°F)   |
| HUMIDITY:                   | 10% to 90%, RHL non-condensing  |
| WEIGHT PER SINGLE SPEAKER:  | 1.75kg (3.9lbs) approx  |
| SHIPPING WEIGHT (FOR PAIR): | 6.1kg (13.5lbs) approx  |
| INSTALLATION DIMENSIONS:    | Mounting depth: 10.7cm (4.2")<br>External diameter: 19.5cm (7.68")<br>Cutout diameter: 16.7cm (6.57") |
| ACCESSORIES:                | Installation bracket, safety cord attached to grill, ceiling mounting kit                             |
| COLOR:                      | White   |