

Epson WorkForce Pro WF-3825DWF Inkjet A4 4800 x 2400 DPI 21 ppm Wi-Fi

Brand : Epson

Product family: WorkForce Pro **Product code:** C11CJ07404

Product name : WF-3825DWF

Print, Scan, Copy, Fax, PrecisionCore Print Head, A4, 21ppm/10ppm, Ethernet, Wi-Fi, 8.8 kg
 Epson WorkForce Pro WF-3825DWF. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 4800 x 2400 DPI, Print speed (colour, normal quality, A4/US Letter): 10 ppm. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A4. Wi-Fi. Product colour: Black



Printing		Network	
Duplex printing mode	Auto	Wi-Fi *	✓
Print technology *	Inkjet	Ethernet LAN *	✓
Printing *	Colour printing	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Duplex printing *	✓	Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP
Maximum resolution *	4800 x 2400 DPI	Mobile printing technologies	Epson Connect, Epson iPrint, Apple AirPrint, Mopria Print Service
Print speed (black, normal quality, A4/US Letter) *	21 ppm	Performance	
Print speed (colour, normal quality, A4/US Letter)	10 ppm	Card reader integrated	✗
Print speed (ISO/IEC 24734) black	21 ppm	Design	
Print speed (ISO/IEC 24734) colour	10 ppm	Product colour *	Black
Duplex print speed (black, normal quality, A4/US Letter)	12 ppm	Market positioning *	Home & office
Duplex print speed (colour, normal quality, A4/US Letter)	7 ppm	Built-in display *	✓
Duplex print speed (ISO/IEC 24734, A4) black	12 ppm	Display	LCD
Duplex print speed (ISO/IEC 24734, A4) colour	7 ppm	Display diagonal	6.86 cm (2.7")
Scanning		Touchscreen	✓
Scanning *	Colour scanning	Colour display	✓
Optical scanning resolution *	1200 x 1200 DPI	Power	
Optical scanning resolution (ADF)	1200 x 1200 DPI	Power consumption (copying)	17 W
Scan technology	CIS	Power consumption (ready)	6.2 W
Image formats supported	BMP, JPEG, TIFF, PNG	Power consumption (off)	0.2 W
Document formats supported	PDF	System requirements	
Fax		Windows operating systems supported	Windows 8.1, Windows 8.1 x64, Windows XP Professional x64, Windows XP
Faxing *	Colour faxing	Mac operating systems supported	✓
Fax transmission speed	3 sec/page		

Fax		System requirements	
Modem speed	33.6 Kbit/s	Linux operating systems supported	Ubuntu 15.10
Fax memory	180 pages	Weight & dimensions	
Fax speed dialing (max numbers)	100	Width	425 mm
Fax forwarding	✓	Depth	378 mm
Fax forwarding to	PC	Height	249 mm
Fax delayed sending	✓	Weight	8.8 kg
Error Correction Mode (ECM)	✓	Packaging data	
Features		Package width	433 mm
Maximum duty cycle *	26000 pages per month	Package depth	475 mm
Number of print cartridges *	4	Package height	315 mm
Printing colours *	Black, Cyan, Magenta, Yellow	Package weight	10.7 kg
Country of origin	Indonesia	Quantity per pack	1 pc(s)
Input & output capacity		Packaging content	
Total number of input trays *	1	Cartridge(s) included	✓
Total output capacity *	80 sheets	Cables included	AC
Auto document feeder (ADF)	✓	Drivers included	✓
Auto document feeder (ADF) input capacity	35 sheets	Warranty card	✓
Auto document feeder (ADF) output capacity	35 sheets	Bundled software	Presto! Page Manager 9
Maximum input capacity	250 sheets	Logistics data	
Paper handling		Harmonized System (HS) code	84433100
Maximum ISO A-series paper size *	A4	Pallet gross weight	0 g
Paper tray media types *	Plain paper	Products per pallet layer	2 pc(s)
ISO A-series sizes (A0...A9) *	A4, A5, A6	Products per pallet	12 pc(s)
ISO B-series sizes (B0...B9)	B5	Pallet weight (UK)	0 g
Non-ISO print media sizes	Legal, Letter	Products per pallet layer (UK)	4 pc(s)
Envelopes sizes	10, C6, DL	Products per pallet (UK)	24 pc(s)
Paper tray media weight	64 - 256 g/m ²	Other features	
Ports & interfaces		Printing method	Epson PrecisionCore
USB port	✓	Number of users	5 user(s)
		Compatible operating systems	Mac OS 10.8.x, Mac OS X 10.11.x, Mac OS X 10.11.x oder höher, Mac OS X 10.12, Mac OS X 10.13.x, Mac OS X 10.6.8 or later, Ubuntu 15.10, Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 (32/64 Bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows XP Professional x64 Edition SP2 or later, Windows XP SP3, Windows XP SP3 or later (32-bit)
		Ink drop	3.8
		Print head nozzles	800 nozzles black, 256 nozzles per colour
		Supported network protocols	IPv4, IPv6



8715946679792

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date