

## Epson DS-770 II Sheet-fed scanner 600 x 600 DPI A4 White

**Brand :** Epson

**Product code:** B11B262401

**Product name :** DS-770 II

- An industry first with Slow Mode: Scan crumpled, long or fragile documents without increasing file sizes
  - Active Separation Roller System: Prevents tedious double feeds ensuring every piece of paper gets scanned
  - Optional flatbed scanner conversion kit: Enables scanning of items from stamps to passports, books and more
  - Auto Scan Mode: Quickly process physical documents in manageable amounts
  - Optional Network Interface: Easy sharing between users with push scan and pre-defined job profiles
- ReadyScan LED, Ultrasonic Sensor, 600 DPI, USB 3.0, 296x169x176 mm



Scanning		Weight & dimensions	
Maximum scan size *	215.9 x 6096 mm	Width	296 mm
Optical scanning resolution *	600 x 600 DPI	Depth	169 mm
Colour scanning	✓	Height	176 mm
Duplex scanning *	✓	Weight	3.7 kg
Input colour depth	30 bit	Packaging data	
Output colour depth	24 bit	Quantity per pack	1 pc(s)
Input greyscale depth	10 bit	Package width	250 mm
Output greyscale depth	8 bit	Package depth	365 mm
Output monochrome depth	8 bit	Package height	285 mm
ADF scan speed (b/w, A4)	45 ppm	Package weight	4.58 kg
ADF scan speed (colour, A4)	45 ppm	Packaging content	
Duplex ADF scan speed (b/w, A4)	90 ipm	Warranty card	✓
Duplex ADF scan speed (colour, A4)	90 ipm	Cables included	AC
Design		Drivers included	✓
Scanner type *	Sheet-fed scanner	Bundled software	Epson Document Capture (Mac only), Epson Document Capture Pro (Windows only), Epson Document Capture Pro Server (on free download), Epson Scan 2, Presto! BizCard 5.6
Product colour *	White		
Display	LCD		
Built-in display *	✓		
Performance			
Light source	ReadyScan LED		
Scan file formats	JPEG, PDF, TIFF		
Daily duty cycle (max) *	7000 pages		
Scan to	E-mail, FTP, Software, Print, Network folder		
Scan drivers	TWAIN, WIA, ISIS		
Ultrasonic sensor	✓		

Input capacity		System requirements	
Standard input capacity	100 sheets		
Auto document feeder (ADF) input capacity	100 sheets		
Paper handling			
Scanning media types supported	Plastic Card, Post Card(JPN)		
Maximum ISO A-series paper size *	A4	Compatible operating systems	Citrix XenApp 5.0, Citrix XenApp 6.0, Citrix XenApp 7.6 und höher, Linux, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X, Mac OS X 10.6.8, Windows 10, Windows 7, Windows 7, 64-Bit-Version, Windows 8, Windows 8 (32/64 Bit), Windows 8 RT, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2008 (32/64 Bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Vista, Windows Vista, 64-Bit-Version, Windows Server 2003 R2, Windows XP Professional x64 Edition
ISO A-series sizes (A0...A9)	A4, A5, A6		
ISO B-series sizes (B0...B9)	B5, B6		
Letter	✓		
Legal	✓		
Auto Document Feeder (ADF) media weight	27 - 413 g/m <sup>2</sup>		
Maximum scan area (ADF)	215.9 x 6096 mm	Windows operating systems supported	Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows RT, Windows 8.1, Windows 8.1 x64, Windows Vista, Windows Vista x64, Windows XP Professional x64
Minimum scan area (ADF)	50.8 x 50.8 mm		
Ports & interfaces			
USB port *	✓	Mac operating systems supported	✓
USB version	3.2 Gen 1 (3.1 Gen 1)	Linux operating systems supported	✓
Power			
Power supply type *	AC	Server operating systems supported	Windows Server 2008, Windows Server 2008 x64, Windows Server 2008 R2, Windows Server 2012 x64, Windows Server 2012 R2, Windows Server 2003 R2
Power consumption (off)	0.1 W		
Operational conditions			
Operating temperature (T-T)	5 - 35 °C		
Storage temperature (T-T)	-25 - 60 °C		
Operating relative humidity (H-H)	15 - 80%		
Storage relative humidity (H-H)	15 - 85%		
Other features			
Output resolutions	75, 100, 150, 200, 240, 300, 600, 1200 dpi		
Image formats supported	JPEG, TIFF		
Logistics data			
Products per pallet	63 pc(s)		
Country of origin	Indonesia		
Pallet gross weight	0 g		
Products per pallet (UK)	84 pc(s)		
Pallet weight (UK)	0 g		
Harmonized System (HS) code	84716070		



8715946685946

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-MAR-2025. Prints or copies of Information are only valid on the printed Publication date