

Epson TM-M30II 203 x 203 DPI Wired Direct thermal POS printer

Brand : Epson

Product code: C31CJ27122

Product name : TM-M30II



- Iconic design: Stylish, practical design with small footprint and clean lines
- Cost effective: Entry-level model (refreshed version of its predecessor, the TM-m30)
- Fast printing: Increased print speed of 250mm/s
- Direct printing from mobile devices: Without the need to install or update drivers
- Reliable: Epson's tried and trusted build quality

Compact mPOS receipt printer TM-M30II (122): USB + ETHERNET + NES, BLACK, PS, EU
 Epson TM-M30II. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite), Maximum printing width: 8 cm. Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: White

Printing		Operational conditions	
Maximum resolution	203 x 203 DPI	Operating relative humidity (H-H)	10 - 90%
Print speed	250 mm/sec	Storage relative humidity (H-H)	10 - 90%
Print speed (receipt)	250 mm/sec	System requirements	
Printing characters	Text, Graphic, Barcode	Pre-installed software	TMNet WebConfig, ePOS-Device, ePOS-Display, ePOS-Print
Character sets	ANK	Weight & dimensions	
Print technology *	Direct thermal	Width	127 mm
Type *	POS printer	Depth	127 mm
Paper handling		Height	127 mm
Maximum roll diameter	8.3 cm	Weight	1.3 kg
Supported paper width	58 mm - 80 mm (Breite)	Packaging data	
Maximum printing width	8 cm	Quantity per pack	1 pc(s)
Ports & interfaces		Package width	195 mm
USB port *	✓	Package depth	235 mm
USB 2.0 ports quantity	2	Package height	235 mm
USB connector	USB Type-A / USB Type-B	Package weight	2.15 kg
Connectivity technology *	Wired	Packaging content	
Near Field Communication (NFC)	✓	AC adapter included	✓
Network		Print technology	
Ethernet LAN *	✓	Column capacity	48/57
Wi-Fi *	✗	Logistics data	
Features		Pallet weight (UK)	0 g
Sound pressure level (printing)	55 dB	Harmonized System (HS) code	84433210
Mean time between failures (MTBF)	360000 h	Products per master (outer) case	4 pc(s)
Half-cutter	✓	Master (outer) case width	400 mm
Autocutter durability	1.5 million cuts	Master (outer) case length	490 mm
Print head life	150 km	Master (outer) case height	255 mm
Country of origin	Philippines	Master (outer) case gross weight	0 g
Mounting position	Horizontal/Vertical	Products per pallet	128 pc(s)
Wall mountable	✓	Pallet gross weight	0 g
Built-in sensors details	Paper End Sensor, Papier-Sensor	Products per pallet (UK)	192 pc(s)
Design		Technical details	
Product colour *	White	Font styles	ANK
Power		Lifetime	17000000 lines
Power source type *	AC		
Power plug type	Type C		

Operational conditions		Other features	
Operating temperature (T-T)	5 - 45 °C	Buffer size	12 KB
Storage temperature (T-T)	-20 - 60 °C	Mean cycles between failures (MCBF)	65000000
		Print head life	150.000.000 Impulse



8715946684796

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date