## be quiet! Pure Base 600 Window Midi Tower musta, Oranssi

Tuotemerkki : be quiet!

Tuotekoodi: BGW20





Tuotteen nimi : Pure Base 600 Window

be quiet! Pure Base 600 Window. Kotelo: Midi Tower, Malli: PC, Tuotteen väri: musta, Oranssi. Virtalähteen sijainti: Alapuolella, Tuettujen virtalähteiden malli: ATX. Asennettuja tuulettimia edessä: 1x 140 mm, Etutuuletinten tuetut koot: 120,140 mm, Asennettuja takatuulettimia: 1x 120 mm. Tuetut HDDkoot: 2.5,3.5". Tuotteen leveys: 220 mm, Tuotteen syvyys: 492 mm, Tuotteen korkeus: 470 mm

## Cooling Design ABS synthetics, Plastic, Steel, 120,140 mm Front fans diameters supported Material Tempered glass Rear fans installed 1x 120 mm Form factor \* Midi Tower Number of rear fans supported 1 Type \* PC (max) 120 mm Product colour \* Black, Orange Rear fans diameters supported Supported motherboard form Number of top fans supported ATX, micro ATX, Mini-ITX З factors <sup>3</sup> (max) 3 120,140 mm Number of 3.5" bays \* Top fans diameters supported 2 Number of 5.25" bays \* Maximum airflow 55.8 cfm Number of 2.5" bays 8 Noise level (high speed) 17.1 dB 3 Number of internal 3.5" bays Fan rated current 0.09 A 2 Number of external 5.25" bays Front radiator sizes supported 120,140,240,280,360 mm 7 Number of expansion slots Rear radiator sizes supported 120 mm Side window Top radiator sizes supported 120,240,360 mm Suitable for Gaming Storage Anti-dust filter Supported HDD sizes \* 2.5,3.5" Cable management Weight & dimensions LED indicators Width 220 mm Maximum CPU cooler height 16.5 cm Depth 492 mm Maximum graphics card length 42.5 cm Height 470 mm Maximum PSU length 21 cm Weight 8.45 kg CE, RoHS Certification Material thickness 1 mm Power supply Packaging data Power supply included \* x 280 mm Package width Power supply location Bottom 515 mm Package depth Supported power supply form Package height 565 mm ATX factors Package weight 9.84 kg Ports & interfaces Logistics data Audio input 1 Harmonized System (HS) code 84733080 Audio output Other features USB 3.2 Gen 1 (3.1 Gen 1) Type-A 2 Fan connector 3-pin ports quantity Mean time between failures (MTBF) 80000 h Cooling

Front fans installed

1x 140 mm

## Cooling

Number of front fans supported 1 (max)



4260052185438

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.