

be quiet! Pure Base 600 Window Midi Tower musta

Tuotemerkki : be quiet!

Tuotekoodi: BGW21

Tuotteen nimi : Pure Base 600 Window

be quiet! Pure Base 600 Window. Kotelo: Midi Tower, Malli: PC, Tuotteen väri: musta. Virtalähteen sijainti: Alapuolella, Tuettujen virtalähteiden malli: ATX. Asennettuja tuulettimia edessä: 1x 140 mm, Etutuuletintien tuetut koot: 120,140 mm, Asennettuja takatuulettimia: 1x 120 mm. Tuettut HDD-koot: 2,5,3,5". Tuotteen leveys: 220 mm, Tuotteen syvyys: 492 mm, Tuotteen korkeus: 470 mm



Design		Cooling	
Material	ABS synthetics, Plastic, Steel, Tempered glass	Front fans diameters supported	120,140 mm
Form factor *	Midi Tower	Rear fans installed	1x 120 mm
Type *	PC	Number of rear fans supported (max)	1
Product colour *	Black	Rear fans diameters supported	120 mm
Supported motherboard form factors *	ATX, micro ATX, Mini-ITX	Number of top fans supported (max)	3
Number of 3.5" bays *	3	Top fans diameters supported	120,140 mm
Number of 5.25" bays *	2	Maximum airflow	55.8 cfm
Number of 2.5" bays	8	Noise level (high speed)	17.1 dB
Number of internal 3.5" bays	3	Fan rated current	0.09 A
Number of external 5.25" bays	2	Front radiator sizes supported	120,140,240,280,360 mm
Number of expansion slots	7	Rear radiator sizes supported	120 mm
Side window	✓	Top radiator sizes supported	120,240,360 mm
Suitable for	Gaming	Storage	
Anti-dust filter	✓	Supported HDD sizes *	2.5,3.5"
Cable management	✓	Weight & dimensions	
LED indicators	✓	Width	220 mm
Maximum CPU cooler height	16.5 cm	Depth	492 mm
Maximum graphics card length	42.5 cm	Height	470 mm
Maximum PSU length	21 cm	Weight	8.45 kg
Certification	CE, RoHS	Material thickness	1 mm
Power supply		Packaging data	
Power supply included *	✗	Package width	280 mm
Power supply location	Bottom	Package depth	515 mm
Supported power supply form factors	ATX	Package height	565 mm
		Package weight	9.84 kg
Ports & interfaces		Logistics data	
Audio input	✓	Harmonized System (HS) code	84733080
Audio output	✓	Other features	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Fan connector	3-pin
Cooling		Mean time between failures (MTBF)	80000 h
Front fans installed	1x 140 mm		

Cooling

Number of front fans supported
(max) 1



4260052185445

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date