
be quiet! TFX POWER 3 300W Bronze virtalähdeyksikkö 20+4 pin ATX musta

Tuotemerkki : be quiet! Tuotekoodi: BN322

Tuotteen nimi: TFX POWER 3 300W Bronze







Total power * 300 W Floppy disk drive cable length 60 cm Peak power 350 W Cabling type Non-Modular AC input voltage * 100 - 240 V Performance 200 - 240 V Purpose * PC Purpose * PC Maximum input current (@110V) 4 A Purpose * PC Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power factor 15 A Power supply unit (PSU) form factor TFX Power supply unit (PSU) form factor 15 A Power supply unit (PSU) form fa				
Peak power 350 W Cabling type Non-Modular AC input voltage* 100 - 240 V Performance AC input voltage* 50 - 60 Hz 30 PLUS certification* 80 PLUS Bronze Input current 4/1.5 A Purpose* PC Maximum input current (@120V) 4 A Power supply unit (PSU) form factor TTX Power Factor Correction (PFC) type Active EPS version 2.52 Combined power (+3.3V) 85 W Noise level 29.1 dB Combined power (+5V) 300 W Bearing technology ERF Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+12V1) 2.5 A Cooling type Active Max output current (+12V1) 3.3 A Cooling type Active Max output current (+5V5b) 16 A Active Active Max output current (+5V5b) 2.5 A Cooling type Active Hold time 2 ver current, Over power, Over voltage, Short circuit, Under vo	Power		Ports & interfaces	
AC input voltage * 100 - 240 V	Total power *	300 W	Floppy disk drive cable length	60 cm
AC input frequency	Peak power	350 W	Cabling type	Non-Modular
Input current 4/1.5 A 80 PLUS certification* 80 PLUS Bronze Maximum input current (@110V) 4 A Purpose * PC Maximum input current (@210V) 4 A Power supply unit (PSU) form factor TTX Power Factor Correction (PFC) type Active EPS version 2.92 Combined power (+3.3V) 85 W Noise level 29.1 dB Combined power (+5V) 85 W Mean time between failures (MTBF) 100000 h Max output current (+12V1) 25 A Safety CE, CB, TÜV, CU Max output current (+12V1) 25 A Design Found t colour Black Max output current (+12V1) 0.3 A Product colour Black Max output current (+12V5) 0.3 A Product colour Black Max output current (+12V5) 0.3 A Product colour Black Max output current (+12V5) 0.5 A Number of fans 1 fan(s) Power protection features Over current, Over power, Over power, Over polate, Short circuit, Under voltage Weight & dimensions Worlds (included tine) 20+4 pin ATX Heig	AC input voltage *	100 - 240 V	Performance	
Input current	AC input frequency		80 PLUS certification *	80 PLUS Bronze
Maximum input current (@110Y) 4 A Power supply unit (PSU) form factor TFX Power factor 0.96 ATX version 2.52 Power Factor Correction (PFC) type Active EPS version 2.92 Combined power (+3.3Y) 85 W Noise level 29.1 dB Combined power (+12V) 300 W Bearing technology Rifle Combined power (+13.3Y) 16 A Max nutput current (F12V) 100000 h Max output current (+12V1) 25 A Max output current (F12V) 0.3 A CE, CB, TÜV, CU Max output current (+15V) 0.3 A Cooling type Active Max output current (F15V) 2.5 A Product colour Black Max output current (F15V) 0.3 A Cooling type Active Max output current (F15V) 0.3 A Cooling type Active Max output current (F15V) 0.3 A Number of fans 1 fan(s) Mericiciency 8.6.% Number of fans 1 fan(s) Power protection features 0.4.9 Weight & dimensions Weight & dimensions	Input current	4/1.5 A		
Maximum input current (@220V) 1.5 A ITA Power factor 0.96 ATX version 2.52 Power Factor Correction (PFC) type Active EPS version 2.92 Combined power (+3.3V) 85 W Noise level 29.1 dB Combined power (+12V) 300 W Bearing technology Rifle Combined power (+12V) 85 W Mean time between failures (MTBF) 100000 h Max output current (+12V1) 25 A Safety CE, CB, TÜV, CU Max output current (+12V1) 25 A Design CE, CB, TÜV, CU Max output current (+12V1) 0.3 A Product colour Black Max output current (+12V1) 0.3 A Cooling type Active Max output current (+12V) 0.3 A Cooling type Active Max output current (+12V) 0.3 A Cooling type Active Max output current (+12V) 0.3 A Cooling type Active Max output current (+12V) 0.3 A Winder type (Mission) 8 cm Efficiency Were current, Over prower own (Mission) <td< td=""><td>Maximum input current (@110V)</td><td></td><td>•</td><td></td></td<>	Maximum input current (@110V)		•	
Power Factor Correction (PFC) type Active PSV version 2.92 Combined power (+3.3V) 85 W Noise level 29.1 dB Combined power (+12V) 300 W Bearing technology Rifle Combined power (+12V) 85 W Mean time between failures (MTBF) 100000 h Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+12V1) 25 A Design Versign Max output current (+5V9) 16 A Design Versign Max output current (+5V9b) 2.5 A Cooling type Active Max output current (+5V9b) 2.5 A Cooling type Active Max output current (+5V9b) 2.5 A Cooling type Active Hold time 22 ms Fan diameter 8 cm Woldth time 8 cm Width 85 mm Ports & interfaces Weight & dimensions Width 85 mm Ports & interfaces 20+4 pin ATX Height 65 mm Motherboard power connector * 20+4 pin ATX Height 90 mm </td <td>Maximum input current (@220V)</td> <td></td> <td>*</td> <td>TFX</td>	Maximum input current (@220V)		*	TFX
Combined power (+3.3V) 85 W Noise level 29.1 dB Combined power (+12V) 300 W Bearing technology Rifle Combined power (+5V) 85 W Mean time between failures (MTBF) 100000 h Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+5V) 16 A Design Forduct colour Black Max output current (+5Vsb) 2.5 A Cooling type Active Max output current (+5Vsb) 2.5 A Cooling type Active Max output current (+5Vsb) 2.5 A Cooling type Active Max output current (+5Vsb) 2.5 A Cooling type Active Hold time 2 ms Fan diameter 8 cm Weight More Mactive Hold time 2 ms Mactive Mactive Weight More Mactive Mactive Hold time 2 ms Mactive Mactive Hold time 2 ms Mactive Mactive More current, Over current, Over current, Over c			ATX version	2.52
Combined power (+12V) 300 W Bearing technology Rifle Combined power (+5V) 85 W Mean time between failures (MTBF) 100000 h Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+12V1) 25 A Max output current (+12V1) 0.3 A Product colour Black Max output current (+5V) 16 A Product colour Black Max output current (+5Vsb) 2.5 A Cooling type Active Hold time 22 ms Fan diameter 8 c m Hold time 22 ms Fan diameter 1 fan(s) Fefficiency 86.4% Number of fans 1 fan(s) Pover current, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces Veight & dimensions Width 85 mm Depth 175 mm Motherboard power connector * 20+4 pin ATX Height 65 mm Motherboard power cable length 35 c m Weight Weight 900 g SATA power cable length 300,450,600 mm Peripheral (Molex) power connectors (4-pin) * Package depth Package height 1.24 kg Peripheral (Molex) power cable length Package weight 1.24 kg Peripheral (Molex) power cable length Package weight 40 cm PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 Sustainability compliance ✓ CPU power cable length 55 cm Nother David Package Sustainability certificates ENERGY STAR, ErP			EPS version	2.92
Combined power (+5V) 85 W Mean time between failures (MTBF) 100000 h Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+12V1) 25 A Max output current (+5V) 16 A Product colour Black Max output current (+5V) 0.3 A Cooling type Active Max output current (+5Vbb) 2.5 A Cooling type Active Hold time 22 ms Fan diameter 8 cm Hold time 22 ms Fan diameter 8 cm Hold time 22 ms Fan diameter 8 cm Hold time 86.4% Number of fans 1 fan(s) Power protection features Verturent, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces Width 85 mm Depth 175 mm Hotherboard power connector 3 Scm Weight 800 g Number of SATA power connector 3 SATA power cable length 300,450,600 mm Package width 900 g Peripheral (Molex) power connectors (4-pin) Package height 1.24 kg PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 Scm Sustainability certificates ENERGY STAR, ErP	• • •		Noise level	29.1 dB
Max output current (+3.3V) 16 A Safety CE, CB, TÜV, CU Max output current (+12V1) 25 A Max output current (+5V) 16 A Max output current (+12V) 0.3 A Product colour Black Max output current (+5V) 15 A Max output current (+5V) 15 A Max output current (+5V) 16 A Max output	•		Bearing technology	Rifle
Max output current (+12V1) 25 A Max output current (+5V) 16 A Max output current (-12V) 0.3 A Max output current (+5Vsb) 2.5 A Cooling type Active Refriciency 86.4% Number of fans 1 fan(s) Meight & dimensions Width 85 mm Ports & interfaces Motherboard power connector * 20+4 pin ATX Height 65 mm Motherboard power cable length 35 cm Weight 900 g Number of SATA power connectors 3 SATA power cable length 900,450,600 mm Peripheral (Molex) power cable length Package width 159 mm Peripheral (Molex) power cable length Package depth 80 mm Peripheral (Molex) power cable length Package weight 1.24 kg PCI Express power connectors (6+2 pin) 40 cm PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 Sustainability compliance ✓ CPU power cable length 35 cm Sustainability certificates ENERGY STAR, ErP	1 , ,		Mean time between failures (MTBF)	100000 h
Max output current (+5V) 16 A Max output current (-12V) 0.3 A Max output current (+5Vsb) 2.5 A Hold time 22 ms Efficiency 86.4% Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces	•		Safety	CE, CB, TÜV, CU
Max output current (-12V) Max output current (+5Vsb) 2.5 A Cooling type Active Ac			Design	
Max output current (+5Vsb) 2.5 A Solution of time 2.2 ms Fan diameter 8 cm Number of fans 1 fan(s) Weight & dimensions Width 85 mm Depth 175 mm Motherboard power connector 20+4 pin ATX Motherboard power cable length Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors Connectors (4-pin) * Peripheral (Molex) power cable Relight Ports & package weight Peripheral (Molex) power cable Relight Ports & package weight Ports & interfaces Active Render of Sat Am diameter Residue & dimensions Weight & dimensions Width Residue & dimensions Weight Residue & dimensions Weight Residue & dimensions Weight Residue & dimensions Weight Residue & dimensions Width Residue & dimensions Weight Residue & dimensions Width Residue & dimensions Weight Residue & dimensions Weight Residue & dimensions Residue & dimensions Weight Residue & dimensions Residue & dimensions Weight Residue & dimensions Weight & dimensions Weight Residue & dimensions Residue & dimensio	•		Product colour	Black
Fan diameter 8 cm Hold time 22 ms Efficiency 86.4% Number of fans 1 fan(s) Number of fans 1 fan(s) Number of fans 5 mm Number of fans 5 mm Number of fans 65 mm Number of sATA power connector 20+4 pin ATX Height 65 mm Number of SATA power connectors 3 month of sata peripheral (Molex) power cable length 300,450,600 mm Peripheral (Molex) power cable length 7 package depth 80 mm Peripheral (Molex) power cable length 800,450 mm Peripheral (Molex) power cable length 40 cm PCI Express power connectors (6+2 pin) PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 Sustainability certificates ENERGY STAR, ErP				
Efficiency 86.4% Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces Ports & interfaces Ports & interfaces Motherboard power connector * 20+4 pin ATX	, ,		5 ,,	
Power protection features Over current, Over power, Over voltage, Short circuit, Under voltage Ports & interfaces Motherboard power connector * 20+4 pin ATX Motherboard power cable length ADD, 450,600 mm Peripheral (Molex) power cable length Peripheral (Molex) power cable Peripheral (Molex				
Ports & interfaces Nothage, Short circuit, Under voltage Ports & interfaces Notherboard power connector * 20+4 pin ATX	Efficiency		Wainht C dimanaiana	- 127
Ports & interfaces Motherboard power connector * 20+4 pin ATX Height 65 mm Motherboard power cable length 35 cm Weight 900 g Number of SATA power connectors 3 SATA power cable length 300,450,600 mm Peripheral (Molex) power connectors (4-pin) * 2 Peripheral (Molex) power cable length 80 mm Peripheral (Molex) power cable length 80 mm Package weight 1.24 kg Package weight 1.24 kg Package weight 1.24 kg Package type Box Package typ	Power protection features	•	9	
Motherboard power connector * 20+4 pin ATX Height 65 mm Motherboard power cable length 35 cm Weight 900 g Number of SATA power connectors 3 SATA power cable length 300,450,600 mm Peripheral (Molex) power connectors (4-pin) * 2 Peripheral (Molex) power cable length 80 mm Peripheral (Molex) power cable length Package height 215 mm Package weight 215 mm Package weight 1.24 kg Package weight 1.24 kg Package type Box Package type Box Technical details CPU P4 connector (4-pin) 1 CPU power cable length 35 cm Sustainability compliance ✓ Sustainability certificates ENERGY STAR, ErP	Ports & interfaces			
Motherboard power cable length Number of SATA power connectors SATA power cable length Peripheral (Molex) po		20±4 nin ATY		
Number of SATA power connectors SATA power cable length Peripheral (Molex) power connectors (4-pin) * Peripheral (Molex) power cable length Package depth Package height Package weight Package weight Package weight Package type Box Package type Box Pechnical details CPU P4 connector (4-pin) CPU power cable length Sustainability compliance CPU power cable length Sustainability certificates ENERGY STAR, ErP	•	·	•	
SATA power cable length 300,450,600 mm Peripheral (Molex) power connectors (4-pin) * Peripheral (Molex) power cable length 300,450 mm Peripheral (Molex) power cable length Package depth 80 mm Package height 215 mm Package weight 1.24 kg PCI Express power connectors (6+2 pin) PCI Express power cable length 40 cm Technical details CPU P4 connector (4-pin) 1 Sustainability compliance CPU power cable length 35 cm Sustainability certificates ENERGY STAR, ErP				300 g
Peripheral (Molex) power connectors (4-pin) * 2 Package depth 80 mm Peripheral (Molex) power cable length 300,450 mm Peripheral (Molex) power cable length Package height 215 mm Package weight 1.24 kg Package type Box Package type Box Package type Box Package type Sustainability compliance CPU P4 connector (4-pin) 1 Sustainability compliance CPU power cable length 35 cm Sustainability certificates ENERGY STAR, ErP	SATA power cable length	300,450,600 mm		
Peripheral (Molex) power cable length 300,450 mm Package height 215 mm Package weight 1.24 kg PCI Express power connectors (6+2 pin) PCI Express power cable length 40 cm PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 Sustainability compliance ✓ CPU power cable length 35 cm Sustainability certificates ENERGY STAR, ErP	Peripheral (Molex) power connectors (4-pin) *	2	-	
PCI Express power connectors (6+2 pin) PCI Express power cable length PCI Express power cable length 40 cm Technical details CPU P4 connector (4-pin) CPU power cable length 35 cm Package type Box Technical details Sustainability compliance ✓ CPU power cable length Sustainability certificates ENERGY STAR, ErP	Peripheral (Molex) power cable	300,450 mm	5 5	
pin) PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 CPU power cable length 35 cm Technical details Sustainability compliance ✓ Sustainability certificates ENERGY STAR, ErP	•			•
PCI Express power cable length 40 cm CPU P4 connector (4-pin) 1 Sustainability compliance CPU power cable length 35 cm Sustainability certificates ENERGY STAR, ErP	pin)	1	3 ,1	507
CPU power cable length 35 cm Sustainability certificates ENERGY STAR, ErP	PCI Express power cable length	40 cm	Technical details	
France congress	CPU P4 connector (4-pin)	1	Sustainability compliance	✓
Floppy drive power connector 1 Compliance certificates RoHS, WEEE	CPU power cable length	35 cm	Sustainability certificates	ENERGY STAR, ErP
	Floppy drive power connector	1	Compliance certificates	RoHS, WEEE

Logistics data

Shipping (inner) case length	47.4 cm
Shipping (inner) case width	27.5 cm
Shipping (inner) case height	19.5 cm
Products per shipping (inner) case	6 pc(s)
Shipping (inner) case gross weight	8.25 kg
Harmonized System (HS) code	84733020



4260052188286

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.