

BenQ LH890UST data projector Ultra short throw projector 4000 ANSI lumens DLP 1080p (1920x1080) White

Brand : BenQ Product code: 9H.JJD77.3HE

Product name: LH890UST

- Ultra short-throw ratio
- BlueCore laser technology for superb image quality
- IP5X dustproof mechanism reducing maintenance costs

4000lms 1080P Education, DLP, 3000000:1, HDMI, VGA, Composite, S-Video

BenQ LH890UST. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Laser, Service life of light source: 20000 h. Fixed focal length: 3.35 mm, Zoom type: Fixed, Throw ratio: 0.23:1. Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Supported video modes: 1080p. Serial interface type: RS-232, HDMI

version: 1.4b





Projector		Storage	
Projector brightness *	4000 ANSI lumens DLP 1080p (1920x1080) 3000000:1	Card reader integrated *	×
Projection technology * Projector native resolution * Contrast ratio (typical) *		Features	
		Interactive *	✓
Native aspect ratio *	16:9	Interactive input supported	Interactive pen/Touch
Number of colours	1.07 billion colours	Noise level (economic mode)	32 dB
Keystone correction, horizontal	-20 - 20°	HDCP	✓
Keystone correction, vertical	-20 - 20°	Noise level *	35 dB
Matrix size	1.65 cm (0.65")	Certification	IP5X
Light source		Multimedia	
Light source type *	Laser	Built-in speaker(s) *	✓
Service life of light source *	20000 h	RMS rated power	10 W
Lens system		Number of built-in speakers	1
Fixed focal length	3.35 mm	TV tuner integrated	×
Zoom type	Fixed	Design	
Throw ratio	0.23:1	Market positioning *	Education
Offset	118.8%	Product type *	Ultra short throw projector
Video		Product colour *	White
Full HD *	✓	Placement	Ceiling, Desktop, Wall
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200	LED indicators	✓
Supported video modes	(MILYCA)	Power	
	10000	Power source *	AC
Ports & interfaces		Power consumption (typical) *	358 W
HDMI version	1.4b	Power consumption (standby) *	0.5 W
S-Video inputs quantity	1	AC input voltage	100 - 240 V
USB 2.0 ports quantity Mini-USB 2.0 ports quantity	1 2	AC input frequency	50 - 60 Hz
Milli-03b 2.0 ports qualitity	۷		

Ports & interfaces		Operational conditions	
Headphone outputs	1	Operating temperature (T-T)	0 - 35 °C
Microphone in	RS-232 atity * 2 2 1	Weight & dimensions	
Serial interface type * VGA (D-Sub) ports quantity * HDMI ports quantity * Composite video in *		Width Depth Height Weight *	502.1 mm 399.3 mm 164.5 mm 9.06 kg
DVI port *	×	Packaging content	
Network		Remote control included *	√
Ethernet LAN * Ethernet LAN (RJ-45) ports	1	Remote control type Batteries included Cables included Mounting brackets included	IR ✓ AC, VGA ✓
		Logistics data	
		Harmonized System (HS) code	85286200

