

## Epson EB-L630U dataprojektori Vakioprojektori 6200 ANSI lumenia 3LCD WUXGA (1920x1200) Valkoinen

**Tuotemerkki :** Epson

**Tuotekoodi:** V11HA26040

**Tuotteen nimi :** EB-L630U



### EB-L630U

Epson EB-L630U. Projektorin kirkkaus: 6200 ANSI lumenia, Projektioteknologia: 3LCD, Projektorin oletusresoluutio: WUXGA (1920x1200). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 30000 h. Tarkennus: Ohje, Polttovälialue: 20 - 31.8 mm, Aukkoalue (F-F): 1,5 - 1,7. Videon käsittely: 10 bittiä, Videon väritilat: Elokvateatteri, Dynaaminen, Esitys, sRGB, DICOM-tilannetila, Multi-projection. Sarjaliitännän tyyppi: RS-232C, HDMI/liitäntätyyppi: Täysikokoinen

Projector		Features	
Smart projector *	✗	Noise level (economic mode)	27 dB
Screen size compatibility *	1270 - 12700 mm (50 - 500")	HDCP	✓
Projection distance	1.44 - 23.84 m	Noise level *	38 dB
Projection distance (wide)	1.4 - 14.8 m	Country of origin	Philippines
Projection distance (tele)	2.4 - 23.8 m	Password protection	✓
Projector brightness *	6200 ANSI lumens	Multimedia	
Projection technology *	3LCD	Built-in speaker(s) *	✓
Projector native resolution *	WUXGA (1920x1200)	RMS rated power	10 W
Contrast ratio (typical) *	2500000:1	Number of built-in speakers	1
Native aspect ratio *	16:10	Design	
Number of colours	1.07 billion colours	Market positioning *	Presentation
Projector brightness (economic mode)	4340 ANSI lumens	Product type *	Standard throw projector
Keystone correction, horizontal	-30 - 30°	Product colour *	White
Keystone correction, vertical	-30 - 30°	Placement	Ceiling, Desktop
Matrix size	1.7 cm (0.67")	Cable lock slot	✓
Light source		Cable lock slot type	Kensington
Light source type *	Laser	Display	
Service life of light source *	20000 h	Built-in display *	✗
Service life of light source (economic mode)	30000 h	Power	
Lens system		Power source *	AC
Focus *	Manual	Power consumption (typical) *	345 W
Focal length range	20 - 31.8 mm	Power consumption (standby) *	0.3 W
Aperture range (F-F)	1.5 - 1.7	Power consumption (economy mode)	258 W
Zoom capability	✓	AC input voltage	100-240 V
Zoom type	Manual	AC input frequency	50 - 60 Hz
Zoom ratio	1.6:1	Software	
Throw ratio	1.35 - 2.2:1	Software support	via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol
Horizontal lens shift range	-20 - 20%	Operational conditions	
Vertical lens shift range	-50 - 50%	Storage temperature (T-T)	-10 - 60 °C
Video		Operating relative humidity (H-H)	20 - 80%
Full HD *	✓	Storage relative humidity (H-H)	10 - 90%
Video processing	10 bit		
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection		

Ports & interfaces		Weight & dimensions	
HDMI connector type	Full-size	Width	440 mm
HDBaseT port	✓	Depth	339 mm
USB 2.0 ports quantity	2	Height	136 mm
USB 2.0 Type-B ports quantity	1	Weight *	8.4 kg
Serial interface type *	RS-232C	Package width	540 mm
PC Audio in	✓	Package depth	565 mm
PC Audio out	✓	Package height	210 mm
VGA (D-Sub) ports quantity *	2	Package weight	12.3 kg
HDMI ports quantity *	3	<b>Packaging content</b>	
DVI port *	✗	Remote control included *	✓
AC (power) in	✓	Batteries included	✓
<b>Network</b>		Cables included	AC
Smart TV *	✗	Manual	✓
Ethernet LAN *	✓	Warranty card	✓
Ethernet LAN (RJ-45) ports	1	WLAN adapter included	✓
Wi-Fi *	✓	<b>Technical details</b>	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Sustainability certificates	TCO
Miracast	✓	<b>Logistics data</b>	
<b>Storage</b>		Quantity per pack	1 pc(s)
Card reader integrated *	✗	Products per pallet	14 pc(s)
<b>Features</b>		Pallet gross weight	0 g
Interactive *	✗	Products per pallet (UK)	14 pc(s)
		Pallet weight (UK)	0 g
		Harmonized System (HS) code	85286200
		<b>Other features</b>	
		Supported network protocols	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink



8715946695310

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date