
## QNAP

## QNAP QSW-M408-4C verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Valkoinen

Tuotemerkki: QNAP Tuotekoodi: QSW-M408-4C

Tuotteen nimi: QSW-M408-4C

Management features





	Design			
	Rack mounting *	x		
	Stackable *	×		
	Product colour	White		
	Reset button	✓		
	LED indicators	Activity, Link, Power, Speed, Status		
	Number of fans Electromagnetic compatibility	1 fan(s) CLASS A		
	Performance			
	Noise level	21 dB		
	Power			
	Power source *	AC		
	Power supply included *	✓		
	Number of power supply units	1		
	AC input voltage	100 - 240 V		
	AC input frequency Power consumption (max)	50 - 60 Hz 31.46 W		
u,	Power over Ethernet (PoE)			
	Power over Ethernet (PoE) *	×		
	Operational conditions			
	Operating temperature (T-T)	0 - 40 °C		
	Operating relative humidity (H-H)	5 - 95%		
	Weight & dimensions			
	Width	290 mm		
	Depth	127 mm		
	Height	42.5 mm		
	Weight	1.15 kg		
Packaging content				
	Cables included	AC		

		9	
Switch type *	Managed	Rack mounting *	×
Switch layer	L2	Stackable *	×
Quality of Service (QoS) support	✓	Product colour	White
Web-based management	✓	Reset button	✓
Ports & interfaces		LED indicators	Activity, Link, Power, Speed, Status
Basic switching RJ-45 Ethernet ports quantity *	8	Number of fans Electromagnetic compatibility	1 fan(s) CLASS A
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Gigabit Ethernet (copper) ports	8	Noise level	21 dB
quantity	8	Power	
Combo SFP ports quantity	4	Power source *	AC
Console port	RJ-45	Power supply included *	✓
Network		Number of power supply units	1
	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input voltage	100 - 240 V
Not a d'acceta de els #		AC input frequency	50 - 60 Hz
Networking standards *		Power consumption (max)	31.46 W
		Power over Ethernet (PoE)	
10G support *	✓	Power over Ethernet (PoE) *	×
Copper ethernet cabling technology	pper ethernet cabling technology LX, 1000BASE-T, 1000BASE-T		
Cable types supported	Cat5, Cat5e, Cat6	Operating temperature (T-T)	0 - 40 °C
Full duplex	✓	Operating relative humidity (H-H)	5 - 95%
Flow control support	/	Weight & dimensions	
Spanning tree protocol	<b>✓</b>	Width	290 mm
Auto-negotiation	1	Depth	127 mm
VLAN support	/	Height	42.5 mm
Virtual LAN features	Port-based VLAN, Private VLAN	Weight	1.15 kg
Data transmission		Packaging content	
Switching capacity *	96 Gbit/s	Cables included	AC
Throughput	48 Gbit/s	Quick start guide	✓
MAC address table *	16000 entries	Packaging data	
Jumbo frames support	✓	Package weight	1.57 kg
Jumbo frames	9000		

Security		Certificates	
DHCP features	DHCP client	Certification	CE, FCC, VCCI, BSMI, CCC
Access Control List (ACL) ✓		Logistics data	
IGMP snooping	<b>✓</b>	Harmonized System (HS) code	85176990



4713213516713

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.