## Epson EB-PU1007W Large venue projector 7000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product code: V11HA34940

Product name : EB-PU1007W

## 3LCD, 0.76" with C2 Fine, WUXGA, 1920 x 1200, 16:10, 7000 Lumen

Epson EB-PU1007W. Projector brightness: 7000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focal length range: varies by lens, Zoom type: Auto, Throw ratio: 0.35 - 10.11:1. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709. Serial interface type: RS-232C





| Projector  |  | Design   |  |
|--|--|--|--|
| Projector brightness *<br>Projection technology *<br>Projector native resolution *<br>Contrast ratio (typical) *<br>Native aspect ratio *<br>Number of colours<br>Projector brightness (economic | 7000 ANSI lumens<br>3LCD<br>WUXGA (1920x1200)<br>2000:1<br>16:10<br>1.07 billion colours<br>4900 ANSI lumens | Market positioning *<br>Product type *<br>Product colour *<br>Placement<br>Cable lock slot<br>Cable lock slot type | Presentation<br>Large venue projector<br>White<br>Ceiling, Desktop, Flying frame<br>Kensington |
| mode)  |  | Display  |  |
| Projector brightness (portrait mode)<br>Keystone correction, horizontal  | -30 - 30°  | Built-in display *   | ×  |
| Keystone correction, vertical  | -45 - 45°  | Power  |  |
| Matrix size<br>Heat dissipation  | 1.93 cm (0.76")<br>1465.4 BTU/h  | Power source *<br>Power consumption (typical) *<br>Power consumption (standby) *                                   | AC<br>431 W<br>0.5 W   |
| Light source   |  | Power consumption (economy   | 366 W  |
| Light source type *<br>Service life of light source *<br>Service life of light source  | Laser<br>20000 h<br>30000 h  | mode)<br>AC input voltage<br>AC input frequency  | 100-240 V<br>50 - 60 Hz  |
| (economic mode)  |  | Software   |  |
| Lens system<br>Focal length range<br>Zoom type   | varies by lens<br>Auto   | Software support   | via: Crestron Integrated Partner,<br>Extron IP Link, Extron XTP, AMX<br>Device Discovery       |
| Throw ratio  | 0.35 - 10.11:1   | Operational conditions   |  |
| Interchangeable lens   | 1  | Storage temperature (T-T)  | -10 - 60 °C  |
| Video  |  | Operating relative humidity (H-H)  | 20 - 80%   |
| Analog signal format system *  | Not supported  | Storage relative humidity (H-H)  | 10 - 90%   |
| Full HD *  |  | Weight & dimensions  |  |
| 3D *   | ×  | Width  | 545 mm   |
| Video processing   | 10 bit   | Depth  | 436 mm   |
|  | Cinema, Dynamic, Natural,  | Height   | 189 mm   |
| Video colour modes   | Presentation, DICOM simulation<br>mode, Multi-projection, BT.709   | Weight *   | 16.3 kg  |
|  | mode, Multi-projection, B1.709   | Package width<br>Package depth   | 570 mm<br>760 mm   |
| Ports & interfaces   |  | Package depth<br>Package height  | 270 mm   |
| HDBaseT port<br>USB 2.0 ports quantity<br>USB 2.0 Type-B ports quantity  | 2<br>1   | Package weight   | 21.5 kg  |

| Ports & interfaces   |  | Packaging content  |   |
|--|--|--|---|
| Audio (L/R) in *<br>Serial interface type *<br>VGA (D-Sub) ports quantity *<br>HDMI ports quantity *<br>DVI port * | 1<br>RS-232C<br>1<br>1   | Remote control included *<br>Batteries included<br>Cables included<br>Manual | ✓<br>AC<br>✓  |
|  | •  | Warranty card  | 1   |
| Network<br>Ethernet LAN *<br>Ethernet LAN (RJ-45) ports<br>Storage   | ✓<br>1   | WLAN adapter included<br>Bundled software                                    | ✓<br>Inhalt DIY-App, EasyMP Multi PC<br>Projection, Epson Projektor Content<br>Manager, Epson Projektor<br>Management, Epson Projektor<br>Professional Tool |
| Card reader integrated *   | ×  | Logistics data   |   |
| FeaturesNoise level (economic mode)29 dBHDCP✓Noise level *33 dBCountry of originPhilippinesPassword protection✓    | Quantity per pack<br>Products per pallet<br>Pallet gross weight<br>Products per pallet (UK)<br>Pallet weight (UK)<br>Harmonized System (HS) code | 1 pc(s)<br>14 pc(s)<br>0 g<br>14 pc(s)<br>0 g<br>85286200                    |   |
|  |  | Other features   | HTTPS IPv6 SNMP ESC/VP net  |
|  |  |  |   |

Supported network protocols

HTTPS, IPv6, SNMP, ESC/VP.net, PJLink



8715946697215

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.