

Epson EB-L720U Standard throw projector 7000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product code: V11HA44040

Product name : EB-L720U

Epson EB-L720U. Projector brightness: 7000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode. Serial interface type: RS-232C, HDMI connector type: Full-size



| Projector | | Features | |
|--|--|--|-------------------------------|
| Screen size compatibility * | 1270 - 12700 mm (50 - 500") | Noise level * | 39 dB |
| Projector brightness * | 7000 ANSI lumens | Country of origin | China |
| Projection technology * | 3LCD | Multimedia | |
| Projector native resolution * | WUXGA (1920x1200) | Built-in speaker(s) * | ✓ |
| Contrast ratio (typical) * | 2500000:1 | RMS rated power | 10 W |
| Native aspect ratio * | 16:10 | Number of built-in speakers | 1 |
| Number of colours | 1.07 billion colours | Design | |
| Projector brightness (economic mode) | 4900 ANSI lumens | Product type * | Standard throw projector |
| Vertical scan range | 192 - 240 Hz | Product colour * | White |
| Keystone correction, horizontal | -30 - 30° | Placement | Ceiling, Desktop, Floor, Wall |
| Keystone correction, vertical | -30 - 30° | Cable lock slot | ✓ |
| Matrix size | 1.7 cm (0.67") | Cable lock slot type | Kensington |
| Light source | | Display | |
| Light source type * | Laser | Built-in display * | ✗ |
| Service life of light source * | 20000 h | Power | |
| Service life of light source (economic mode) | 30000 h | Power source * | AC |
| Lens system | | Power consumption (typical) * | 345 W |
| Focus * | Manual | Power consumption (standby) * | 0.3 W |
| Focal length range | 20 - 31.8 mm | Power consumption (economy mode) | 258 W |
| Aperture range (F-F) | 1.5 - 1.7 | AC input voltage | 100-240 V |
| Zoom capability | ✓ | AC input frequency | 50 - 60 Hz |
| Zoom type | Manual | Software | |
| Zoom ratio | 1.6:1 | Software support | |
| Throw ratio | 1.35 - 2.20:1 | via: AMX, Crestron (Network), Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol | |
| Offset | 27% | Operational conditions | |
| Video | | Storage temperature (T-T) | -10 - 60 °C |
| Full HD * | ✓ | Operating relative humidity (H-H) | 20 - 80% |
| Video processing | 10 bit | Storage relative humidity (H-H) | 10 - 90% |
| Video colour modes | Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode | Weight & dimensions | |
| Ports & interfaces | | Width | 440 mm |
| HDMI connector type | Full-size | Depth | 122 mm |
| HDBaseT port | ✓ | | |
| USB 2.0 ports quantity | 1 | | |

| Ports & interfaces | | Weight & dimensions | |
|-------------------------------|--------------------|-----------------------------|-------------------------------|
| USB 2.0 Type-B ports quantity | 1 | Height | 304 mm |
| Serial interface type * | RS-232C | Weight * | 7.8 kg |
| PC Audio in | ✓ | Package width | 540 mm |
| PC Audio out | ✓ | Package depth | 530 mm |
| VGA (D-Sub) ports quantity * | 3 | Package height | 210 mm |
| HDMI ports quantity * | 2 | Package weight | 10.8 kg |
| DVI port * | ✗ | Packaging content | |
| Network | | Remote control included * | ✓ |
| Smart TV * | ✗ | Batteries included | ✓ |
| Ethernet LAN * | ✓ | Cables included | AC, HDMI |
| Ethernet LAN (RJ-45) ports | 1 | Manual | ✓ |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Warranty card | ✓ |
| Wi-Fi * | ✗ | WLAN adapter included | ✓ |
| Storage | | Bundled software | EasyMP Multi PC Projection |
| Card reader integrated * | ✗ | Technical details | |
| Features | | USB display function | 3 in 1: Image / Mouse / Sound |
| Interactive * | ✗ | Sustainability certificates | TCO |
| Noise level (economic mode) | 27 dB | Logistics data | |
| | | Quantity per pack | 1 pc(s) |
| | | Products per pallet | 14 pc(s) |
| | | Pallet gross weight | 0 g |
| | | Products per pallet (UK) | 14 pc(s) |
| | | Pallet weight (UK) | 0 g |
| | | Harmonized System (HS) code | 85286200 |



8715946695587

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-APR-2025. Prints or copies of Information are only valid on the printed Publication date