Epson EB-PU2010B Large venue projector 10000 ANSI lumens 3LCD WUXGA (1920x1200) Black

Brand : Epson **Product code:** V11HA52840

Product name: EB-PU2010B

3LCD, 1.03" with C2 Fine, WUXGA, 1920 x 1200, 16:10, 10000 Lumen Epson EB-PU2010B. Projector brightness: 10000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focal length range: varies by lens, Zoom type: Auto, Throw ratio: 0.35 - 7.41:1. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709. Serial interface type: RS-232C





| Projector | | Design | |
|--|--|---|---|
| Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Projector brightness (economic | 10000 ANSI lumens 3LCD WUXGA (1920x1200) 2000:1 16:10 1.07 billion colours | Market positioning * Product type * Product colour * Placement Cable lock slot Cable lock slot type | Business Large venue projector Black Ceiling, Desktop, Flying frame ✓ Kensington |
| mode) | 7000 ANSI lumens | Display | |
| Projector brightness (portrait mode) | 10000 ANSI lumens | Built-in display * | X |
| Keystone correction, horizontal Keystone correction, vertical Matrix size Heat dissipation | -30 - 30° -45 - 45° 2.62 cm (1.03") 1819 BTU/h | Power Power source * Power consumption (typical) * | AC 535 W |
| Light source | | Power consumption (standby) * Power consumption (economy | 0.5 W |
| Light source type * Service life of light source * Service life of light source (economic mode) | Laser 20000 h 30000 h | mode) AC input voltage AC input frequency Software | 452 W 100-240 V 50 - 60 Hz |
| Lens system | | | via: Crestron Integrated Partner, |
| Focal length range Zoom type | varies by lens Auto | Software support | Extron IP Link, Extron XTP, AMX Device Discovery |
| Throw ratio | 0.35 - 7.41:1 | Operational conditions | |
| Interchangeable lens | ✓ | Storage temperature (T-T) | -10 - 60 °C |
| Video | | Operating relative humidity (H-H) Storage relative humidity (H-H) | 20 - 80% 10 - 90% |
| Analog signal format system * Full HD * | Not supported | Weight & dimensions | |
| 3D * Video processing Video colour modes Ports & interfaces | X 10 bit Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709 | Width Depth Height Weight * Package width Package depth | 545 mm 436 mm 189 mm 16.8 kg 570 mm 765 mm |
| USB 2.0 ports quantity USB 2.0 Type-B ports quantity Audio (L/R) in * | 2 1 1 | Package height Package weight | 270 mm 21.9 kg |

| Ports & interfaces | | Packaging content | |
|--|---|---|--|
| Serial interface type * VGA (D-Sub) ports quantity * HDMI ports quantity * DVI port * | RS-232C 1 1 √ | Remote control included * Batteries included Cables included Manual | ✓ ✓ AC ✓ |
| Network | | Warranty card | ✓ |
| Ethernet LAN * Ethernet LAN (RJ-45) ports | 1 | WLAN adapter included | ✓ Inhalt DIY-App, EasyMP Multi PC Projection, Epson Projektor Content |
| Storage Card reader integrated * | × | Bundled software | Manager, Epson Projektor Management, Epson Projektor Professional Tool |
| Features | | Logistics data | |
| Noise level (economic mode) Preset modes Noise level * Country of origin Password protection | 30 dB Cinema, Presentation, Dynamic 37 dB Philippines ✓ | Quantity per pack Products per pallet Pallet gross weight Products per pallet (UK) Pallet weight (UK) Harmonized System (HS) code | 1 pc(s) 14 pc(s) 0 g 14 pc(s) 0 g 85286200 |
| | | Other features | |
| | | Supported network protocols | HTTPS, IPv6, SNMP, ESC/VP.net, PJLink |



8715946697437

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.