

Epson EB-L630SU data projector Standard throw projector 6000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product code: V11HA29040

Product name : EB-L630SU



Epson EB-L630SU. Projector brightness: 6000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Fixed focal length: 11.8 mm, Zoom type: Auto. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection. Serial interface type: RS-232C

Projector		Features	
Screen size compatibility *	1270 - 5080 mm (50 - 200")	Noise level *	38 dB
Projection distance	0.9 - 3.5 m	Country of origin	Philippines
Projection distance (wide)	0.9 - 3.5 m	Password protection	✓
Projector brightness *	6000 ANSI lumens	Multimedia	
Projection technology *	3LCD	Built-in speaker(s) *	✓
Projector native resolution *	WUXGA (1920x1200)	RMS rated power	10 W
Contrast ratio (typical) *	2500000:1	Number of built-in speakers	1
Native aspect ratio *	16:10	Design	
Number of colours	1.07 billion colours	Market positioning *	Presentation
Projector brightness (economic mode)	4200 ANSI lumens	Product type *	Standard throw projector
Keystone correction, horizontal	-30 - 30°	Product colour *	White
Keystone correction, vertical	-30 - 30°	Placement	Ceiling, Desktop
Matrix size	1.7 cm (0.67")	Cable lock slot	✓
Light source		Cable lock slot type	Kensington
Light source type *	Laser	Display	
Service life of light source *	20000 h	Built-in display *	✗
Service life of light source (economic mode)	30000 h	Power	
Lens system		Power source *	AC
Focus *	Manual	Power consumption (typical) *	345 W
Fixed focal length	11.8 mm	Power consumption (standby) *	0.3 W
Zoom capability	✓	Power consumption (economy mode)	258 W
Zoom type	Auto	AC input voltage	100-240 V
Zoom ratio	1.35:1	AC input frequency	50 - 60 Hz
Throw ratio	0.80:1	Software	
Horizontal lens shift range	-20 - 20%	Software support	via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol
Vertical lens shift range	-50 - 50%	Operational conditions	
Video		Storage temperature (T-T)	-10 - 60 °C
Analog signal format system *	Not supported	Operating relative humidity (H-H)	20 - 80%
Full HD *	✓	Storage relative humidity (H-H)	10 - 90%
3D *	✗	Weight & dimensions	
Video processing	10 bit	Width	440 mm
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection		

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	2	Depth	334 mm
USB 2.0 Type-B ports quantity	1	Height	136 mm
Audio (L/R) in *	1	Weight *	8.4 kg
Serial interface type *	RS-232C	Package width	540 mm
VGA (D-Sub) ports quantity *	3	Package depth	560 mm
HDMI ports quantity *	3	Package height	210 mm
DVI port *	✗	Package weight	12.3 kg
Network		Packaging content	
Ethernet LAN *	✓	Remote control included *	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Batteries included	✓
Wi-Fi *	✓	Cables included	AC
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Manual	✓
Miracast	✓	Warranty card	✓
Storage		WLAN adapter included	✓
Card reader integrated *	✗	Logistics data	
Features		Quantity per pack	1 pc(s)
Noise level (economic mode)	27 dB	Products per pallet	14 pc(s)
HDCP	✓	Pallet gross weight	0 g
		Products per pallet (UK)	14 pc(s)
		Pallet weight (UK)	0 g
		Harmonized System (HS) code	85286200
		Other features	
		Supported network protocols	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink



8715946695358

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date